

ADDENDUM B

Final Remedial Action Plan
DOE-EM/GJ1547
February 2008

Final Design Specifications

Number	Title	Pages
31-00-00 R2	Earthwork	1 – 20
31-00-20 R2	Placement and Compaction of Tailings and Interim Cover	1 – 09
31-00-30 R1	Placement and Compaction of Final Cap Layers	1 – 10
31-32-11 R1	Surface Water Management and Erosion Control	1 – 06
32-11-23 R2	Aggregate and Riprap	1 – 14

FOR EASY NAVIGATION – CLICK ON SECTION NAME / LINK ABOVE

OR USE BOOKMARKS TAB AT LEFT

SECTION TABLE OF CONTENTS

DIVISION 31 - EARTHWORK

SECTION 31 00 00

EARTHWORK

PART 1 GENERAL

- 1.1 REFERENCES
- 1.2 DEFINITIONS
 - 1.2.1 Satisfactory Materials
 - 1.2.2 Unsatisfactory Materials
 - 1.2.3 Degree of Compaction
 - 1.2.4 Rock
 - 1.2.5 Unstable Material
 - 1.2.6 Select Granular Material
 - 1.2.6.1 General Requirements
 - 1.2.6.2 California Bearing Ratio
 - 1.2.7 Pipe Bedding Material
 - 1.2.8 Expansive Soils
 - 1.2.9 Nonfrost Susceptible (NFS) Material
- 1.3 SUBMITTALS
- 1.4 SUBSURFACE DATA
- 1.5 CLASSIFICATION OF EXCAVATION
 - 1.5.1 Topsoil
 - 1.5.2 Common Excavation
 - 1.5.3 Rock Excavation
 - 1.5.4 BLASTING
- 1.6 DEWATERING

PART 2 PRODUCTS

- 2.1 BURIED WARNING AND IDENTIFICATION TAPE
- 2.2 MATERIAL FOR RIP-RAP
- 2.3 PIPE BEDDING MATERIAL
- 2.4 CAPILLARY WATER BARRIER
- 2.5 PIPE CASING
 - 2.5.1 Casing Pipe

PART 3 EXECUTION

- 3.1 GENERAL EXCAVATION
 - 3.1.1 Ditches, Gutters, and Channel Changes
 - 3.1.2 Drainage Structures
 - 3.1.3 Drainage
 - 3.1.4 Dewatering
 - 3.1.5 Trench Excavation Requirements
 - 3.1.5.1 Bottom Preparation
 - 3.1.5.2 Removal of Unyielding Material
 - 3.1.5.3 Removal of Unstable Material
 - 3.1.5.4 Excavation for Appurtenances
 - 3.1.5.5 Jacking, Boring, and Tunneling
 - 3.1.6 Underground Utilities
 - 3.1.7 Structural Excavation

- 3.2 SELECTION OF BORROW MATERIAL
- 3.3 SHORING
 - 3.3.1 General Requirements
 - 3.3.2 Geotechnical Engineer
- 3.4 STOCKPILE AREAS
- 3.5 FINAL GRADE OF SURFACES TO SUPPORT CONCRETE
- 3.6 GROUND SURFACE PREPARATION
 - 3.6.1 General Requirements
 - 3.6.2 Frozen Material
- 3.7 UTILIZATION OF EXCAVATED MATERIALS
 - 3.7.1 Use of Excavated Material as Fill
- 3.8 BURIED TAPE AND DETECTION WIRE
 - 3.8.1 Buried Warning and Identification Tape
- 3.9 BACKFILLING AND COMPACTION
 - 3.9.1 Trench Backfill
 - 3.9.1.1 Replacement of Unyielding Material
 - 3.9.1.2 Replacement of Unstable Material
 - 3.9.1.3 Bedding and Initial Backfill
 - 3.9.1.4 Final Backfill
 - 3.9.2 Backfill for Appurtenances
- 3.10 SPECIAL REQUIREMENTS
 - 3.10.1 Water Lines
 - 3.10.2 Electrical Distribution System
 - 3.10.3 Pipeline Casing
 - 3.10.3.1 Bore Holes
 - 3.10.3.2 Cleaning
 - 3.10.3.3 End Seals
 - 3.10.4 Rip-Rap Construction
 - 3.10.4.1 Stone Placement
- 3.11 EMBANKMENTS
 - 3.11.1 Earth Embankments
 - 3.11.1.1 Waste Cell Perimeter Embankment at Crescent Junction
 - 3.11.1.2 Waste Cell Spoil Material Embankment at Crescent Junction
- 3.12 SUBGRADE PREPARATION
 - 3.12.1 Proof Rolling
 - 3.12.2 Construction
 - 3.12.3 Compaction
 - 3.12.3.1 Subgrade for Railroads
 - 3.12.3.2 Subgrade for Pavements
- 3.13 FINISHING
 - 3.13.1 Subgrade and Embankments
 - 3.13.2 Capillary Water Barrier
 - 3.13.3 Grading Around Structures
- 3.14 TESTING
 - 3.14.1 In-Place Densities
 - 3.14.1.1 In-Place Density Testing of Waste Cell Perimeter Embankment
 - 3.14.1.2 In-Place Density Testing of Waste Cell Spoil Material Embankment
 - 3.14.2 Check Tests on In-Place Densities
 - 3.14.3 Optimum Moisture and Laboratory Maximum Density
 - 3.14.4 Moisture Control
- 3.15 DISPOSITION OF SURPLUS MATERIAL

-- End of Section Table of Contents --

SECTION 31 00 00

EARTHWORK

PART 1 GENERAL

This Earthwork Specification covers most of the earthwork in support of the Moab UMPRA Project, including work at the Moab site, at Crescent Junction, and for the Green River to Crescent Junction Water Line. Earthwork not covered by this specification (covered under separate specifications) includes the Haul Road work at Moab, Placement and Compaction of Tailings and Interim Cover, and Placement and Compaction of Final Cap Layers.

1.1 REFERENCES

The publications listed below form a part of this specification to the extent referenced. The publications are referred to within the text by the basic designation only.

AMERICAN ASSOCIATION OF STATE HIGHWAY AND TRANSPORTATION OFFICIALS
(AASHTO)

- | | |
|--------------|---|
| AASHTO T 99 | (2001; R 2004) Moisture-Density Relations of Soils Using a 2.5-kg (5.5-lb) Rammer and a 305-mm (12-in) Drop |
| AASHTO T 180 | (2001; R 2004) Moisture-Density Relations of Soils Using a 4.54-kg (10-lb) Rammer and a 457-mm (18-in) Drop |
| AASHTO T 224 | (2001; R 2004) Correction for Coarse Particles in the Soil Compaction Test |

ASTM INTERNATIONAL (ASTM)

- | | |
|-------------|---|
| ASTM A 139 | (2004) Electric-Fusion (Arc)-Welded Steel Pipe (NPS 4 and Over) |
| ASTM C 136 | (2006) Standard Test Method for Sieve Analysis of Fine and Coarse Aggregates |
| ASTM C 33 | (2003) Standard Specification for Concrete Aggregates |
| ASTM D 698 | (2000ae1) Laboratory Compaction Characteristics of Soil Using Standard Effort (12,400 ft-lbf/cu ft) |
| ASTM D 1140 | (2000) Amount of Material in Soils Finer than the No. 200 (75-micrometer) Sieve |
| ASTM D 1556 | (2000) Density and Unit Weight of Soil in Place by the Sand-Cone Method |
| ASTM D 1557 | (2002e1) Standard Test Methods for |

	Laboratory Compaction Characteristics of Soil Using Standard Effort (56,000 ft-lbf/cu ft)
ASTM D 1883	(2005) CBR (California Bearing Ratio) of Laboratory-Compacted Soils
ASTM D 2487	(2006) Soils for Engineering Purposes (Unified Soil Classification System)
ASTM D 422	(1963; R 2002e1) Particle-Size Analysis of Soils
ASTM D 4318	(2005) Liquid Limit, Plastic Limit, and Plasticity Index of Soils
ASTM D 6938	(2007b) In-Place Density and Water Content of Soil and Soil-Aggregate by Nuclear Methods (Shallow Depth)
ASTM D 2216	(2005) Laboratory Determination of Water (Moisture) Content of Soil and Rock by Mass (Oven Moisture)
ASTM D 4643	(2000) Determination of Water (Moisture) Content of Soil by the Microwave Oven Heating
ASTM D 4944	(2004) Field Determination of Water (Moisture) Content of Soil by the Calcium Carbide Gas Pressure Tester
ASTM D 4643	(2000) Determination of Water (Moisture) Content of Soil by Direct Heating

AMERICAN WELDING SOCIETY (AWS)

AWS D1.1	(2004) Structural Welding Code - Steel
----------	--

1.2 DEFINITIONS

1.2.1 Satisfactory Materials

Satisfactory materials comprise any materials classified by ASTM D 2487 as GW, GP, GM, GP-GM, GW-GM, GC, GP-GC, GM-GC, SW, SP, SM, SW-SM, SC, SW-SC, CL, ML, and CL-ML. Satisfactory materials for grading comprise stones less than 4 inches, except for fill material for pavements and railroads which comprise stones less than 3 inches in any dimension.

1.2.2 Unsatisfactory Materials

Materials which do not comply with the requirements for satisfactory materials are unsatisfactory. Unsatisfactory materials include man-made fills; trash; refuse; backfills from previous construction; and material classified as satisfactory which contains root and other organic matter or frozen material. Notify the Construction Manager when encountering any contaminated materials.

1.2.3 Degree of Compaction

Degree of compaction required, except as noted in the second sentence, is expressed as a percentage of the maximum density obtained by the test procedure presented in ASTM D 698 or ASTM D 1557 abbreviated as a percent of laboratory maximum density. Since ASTM D 698 and ASTM D 1557 apply only to soils that have 30 percent or less by weight of their particles retained on the 3/4 inch sieve, express the degree of compaction for material having more than 30 percent by weight of their particles retained on the 3/4 inch sieve as a percentage of the maximum density in accordance with AASHTO T 99 or AASHTO T 180 and corrected with AASHTO T 224.

1.2.4 Rock

Solid homogeneous material with firmly cemented, laminated, or foliated masses or conglomerate deposits, neither of which can be removed without systematic drilling and blasting, drilling and the use of expansion jacks or feather wedges, or the use of backhoe-mounted pneumatic hole punchers or rock breakers; also large boulders, buried masonry, or concrete other than pavement exceeding 1/2 cubic yard in volume.

1.2.5 Unstable Material

Unstable materials are too soft or unstable to properly support the utility pipe, conduit, or structure.

1.2.6 Select Granular Material

1.2.6.1 General Requirements

Select granular material consists of materials classified as GW, GP, SW, or SP, or by ASTM D 2487 where indicated. Not more than 30 percent by weight may be finer than No. 200 sieve when tested in accordance with ASTM D 1140.

1.2.6.2 California Bearing Ratio

California Bearing Ratio (CBR) tests are intended to evaluate the strength of pavement subgrade. Perform CBR tests on select granular material in accordance with ASTM D 1883 for a laboratory soaking period of not less than 4 days. Prepare and compact specimens at 95 percent ASTM D 1557 maximum density.

1.2.7 Pipe Bedding Material

Pipe bedding material shall consist of select granular material in accordance with Section 32 11 23, AGGREGATE AND RIPRAP.

1.2.8 Expansive Soils

Expansive soils are defined as soils that have a soil Activity number greater than 1.25, where Activity(Ac) = Plasticity Index / percent finer than .002mm.

1.2.9 Nonfrost Susceptible (NFS) Material

Nonfrost susceptible material is a uniformly graded gravel or washed sand with no more than 3 percent smaller than .002mm.

1.3 SUBMITTALS

Approval is required for submittals with a "G" designation; submittals not having a "G" designation are for information only. All submittals shall be provided to the Construction Manager in accordance with Section 01 33 00 SUBMITTAL PROCEDURES:

SD-01 Preconstruction Submittals

Shoring; G;

Blasting; G;

Submit 15 days prior to starting work.

SD-03 Product Data

Utilization of Excavated Materials;

Rock Excavation

Opening of any Excavation or Borrow Pit

Procedure and location for disposal of unused satisfactory material. Proposed source of borrow material. Notification of encountering unrippable rock in the project. Advance notice on the opening of excavation or borrow areas.

SD-06 Test Reports

Borrow/Fill Material Testing

Compaction Testing

Within 24 hours of conclusion of physical tests, 3 copies of test results, including calibration curves and results of calibration tests.

SD-07 Certificates

Testing

Qualifications of the testing laboratory.

1.4 SUBSURFACE DATA

Subsurface soil boring logs are available for elements of this project. These data represent the best subsurface information available; however, variations may exist in the subsurface between boring locations.

1.5 CLASSIFICATION OF EXCAVATION

Excavation will be designated as topsoil, common excavation, Mancos Shale, or rock excavation.

1.5.1 Topsoil

Topsoil is defined as the top one ft of natural soil at Crescent Junction.

1.5.2 Common Excavation

Common excavation includes all materials not classified as Mancos shale or rock excavation.

1.5.3 Rock Excavation

Include rock excavation with blasting, excavating, grading, disposing of material classified as rock, and the satisfactory removal and disposal of boulders 1/2 cubic yard or more in volume; solid rock; rock material that is in ledges, bedded deposits, and unstratified masses, which cannot be removed without systematic drilling and blasting; firmly cemented conglomerate deposits possessing the characteristics of solid rock impossible to remove without systematic drilling and blasting; and hard materials (see Definitions). Include the removal of any concrete or masonry structures, except pavements, exceeding 1/2 cubic yard in volume that may be encountered in the work in this classification. If at any time during excavation, including excavation from borrow areas, the Contractor encounters material that may be classified as rock excavation, uncover such material and notify the Construction Manager. The Contractor shall not proceed with the excavation of this material until the Construction Manager has classified the materials as common excavation or rock excavation and has taken cross sections as required. Failure on the part of the Contractor to uncover such material, notify the Construction Manager, and allow ample time for classification and cross sectioning of the undisturbed surface of such material will cause the forfeiture of the Contractor's right of claim to any classification or volume of material to be paid for other than that allowed by the Construction Manager for the areas of work in which such deposits occur.

1.5.4 BLASTING

Blasting shall be limited to that required for a quarrying operation to provide rock for the Waste Cell construction at Crescent Junction. At other project locations, blasting to break rock for excavating shall be performed only if no other method of rock removal will work, and only with prior written approval of a blasting plan. The Contractor shall submit a Blasting Plan in conformance with Federal, State, and local safety regulations, prepared and sealed by a registered professional engineer that includes calculations for overpressure and debris hazard. Provide blasting mats and use the non-electric blasting caps. Obtain written approval prior to performing any blasting and notify the Construction Manager 24 hours prior to blasting. Include provisions for storing, handling and transporting explosives as well as for the blasting operations in the plan. The Contractor is responsible for damage caused by blasting operations.

1.6 DEWATERING

Perform dewatering of work areas in accordance with the project plans and specification section 31 32 11, SURFACE-WATER MANAGEMENT AND EROSION CONTROL.

PART 2 PRODUCTS

2.1 BURIED WARNING AND IDENTIFICATION TAPE

Provide polyethylene plastic warning tape manufactured specifically for warning and identification of buried utility lines. Provide tape on rolls,

3 inch minimum width, color coded as specified below for the intended utility with warning and identification imprinted in bold black letters continuously over the entire tape length. Warning and identification to read, "CAUTION, BURIED (intended service) LINE BELOW" or similar wording. Provide permanent color and printing, unaffected by moisture or soil.

Warning Tape Color Codes

[Red:]	[Electric]
[Orange:]	[Telephone and Other Communications]
[Blue:]	[Water Systems]
[Green:]	[Sewer Systems]

2.2 MATERIAL FOR RIP-RAP

Provide filter fabric between soil and riprap in accordance with 31 05 19 GEOTEXTILE and rock conforming to RIPRAP in accordance with 32 11 23 AGGREGATE AND RIPRAP.

2.3 PIPE BEDDING MATERIAL

Provide bedding material consisting of sand, gravel, or crushed rock, open graded with a maximum particle size of 3/8 inch. Compose material of tough, durable particles. Bedding material shall be free of fines passing the No. 200 standard sieve.

2.4 CAPILLARY WATER BARRIER

Provide capillary water barrier of clean, open graded crushed rock, crushed gravel, or uncrushed gravel placed beneath a slab with or without a vapor barrier to cut off the capillary flow of pore water to the area immediately below. Conform to ASTM C 33 for fine aggregate grading with a maximum of 3 percent by weight passing ASTM D 1140, No. 200 sieve.

2.5 PIPE CASING

2.5.1 Casing Pipe

ASTM A 139, Grade B. Match casing size to the outside diameter and wall thickness as indicated on the drawings. Protective coating is not required on casing pipe.

PART 3 EXECUTION

3.1 GENERAL EXCAVATION

Perform excavation of every type of material encountered within the limits of the project to the lines, grades, and elevations indicated on the drawings. Excavate unsatisfactory materials encountered within the limits of the work below grade and replace with satisfactory materials as directed. Dispose of unsatisfactory excavated material in designated waste or spoil areas. During construction, perform excavation and fill in a manner and sequence that will provide proper drainage at all times. Excavate material required for fill or embankment in excess of that produced by excavation within the grading limits from the borrow areas indicated or from other approved areas selected by the Contractor.

3.1.1 Ditches, Gutters, and Channel Changes

Finish excavation of ditches, gutters, and channel changes by cutting

accurately to the cross sections, grades, and elevations shown on the drawings. Do not excavate ditches and gutters below grades shown. Backfill the excessive open ditch or gutter excavation with satisfactory, thoroughly compacted, material or with suitable stone or riprap to grades shown. Dispose of excavated material as shown or as directed, except in no case allow material be deposited a maximum 4 feet from edge of a ditch. Maintain excavations free from detrimental quantities of brush, sticks, trash, and other debris until final acceptance of the work.

3.1.2 Drainage Structures

Make excavations to the lines, grades, and elevations shown, or as directed. Provide trenches and foundation pits of sufficient size to permit the placement and removal of forms for the full length and width of structure footings and foundations as shown. Clean rock or other hard foundation material of loose debris and cut to a firm, level, stepped, or serrated surface. Remove loose disintegrated rock and thin strata. Do not disturb the bottom of the excavation when concrete or masonry is to be placed in an excavated area. Do not excavate to the final grade level until just before the concrete or masonry is to be placed. Where pile foundations are to be used, stop the excavation of each pit at an elevation 1 foot above the base of the footing, as specified, before piles are driven. After the pile driving has been completed, remove loose and displaced material and complete excavation, leaving a smooth, solid, undisturbed surface to receive the concrete or masonry.

3.1.3 Drainage

Provide for the collection and disposal of surface and subsurface water encountered during construction. Completely drain construction site during periods of construction to keep soil materials sufficiently dry. Construct storm drainage features (ponds/basins) at the earliest stages of site development, and throughout construction grade the construction area to provide positive surface water runoff away from the construction activity and provide temporary ditches, swales, and other drainage features and equipment as required to maintain dry soils. It is the responsibility of the Contractor to assess the soil and ground water conditions presented by the plans and specifications and to employ necessary measures to permit construction to proceed.

3.1.4 Dewatering

While the excavation is open, dewater the construction area to limit accumulation of water in the work area and to prevent damage to finished work. Operate dewatering system continuously until construction work below existing water levels is complete.

3.1.5 Trench Excavation Requirements

Excavate trenches as recommended by the manufacturer of the pipe to be installed. Provide vertical trench walls where no manufacturer's printed installation manual is available. Shore trench walls more than 4.5 feet high, cut back to a stable slope (as defined by OSHA 29 CFR 1926), or provide with equivalent means of protection for employees who may be exposed to moving ground or cave in. Excavate trench walls which are cut back to at least the angle of repose of the soil as determined by a professional geotechnical engineer. "Safe trench excavation is at all times the responsibility of the Contractor."

3.1.5.1 Bottom Preparation

Grade the bottoms of trenches accurately to provide uniform bearing and support for the bottom quadrant of each section of the pipe. Excavate bell holes to the necessary size at each joint or coupling to eliminate point bearing. Remove stones of 1 inch or greater in any dimension, or as recommended by the pipe manufacturer, whichever is smaller, to avoid point bearing.

3.1.5.2 Removal of Unyielding Material

Where unyielding material is encountered in the bottom of the trench, remove such material 6 inches below the required grade and replace with suitable materials as provided in paragraph BACKFILLING AND COMPACTION.

3.1.5.3 Removal of Unstable Material

Where unstable material is encountered in the bottom of the trench, remove such material to the depth directed and replace it to the proper grade with select granular material as provided in paragraph BACKFILLING AND COMPACTION.

3.1.5.4 Excavation for Appurtenances

Provide excavation for manholes, catch-basins, inlets, or similar structures sufficient to leave at least 12 inch clear between the outer structure surfaces and the face of the excavation. When concrete or masonry is to be placed in an excavated area, take special care not to disturb the bottom of the excavation. Do not excavate to the final grade level until just before the concrete or masonry is to be placed.

3.1.5.5 Jacking, Boring, and Tunneling

Unless otherwise indicated, provide excavation by open cut except that sections of a trench may be jacked, bored, or tunneled if, in the opinion of the Construction Manager, the pipe, cable, or duct can be safely and properly installed and backfill can be properly compacted in such sections.

3.1.6 Underground Utilities

For work immediately adjacent to or for excavations exposing a utility or other buried obstruction, excavate by hand. Start hand excavation on each side of the indicated obstruction and continue until the obstruction is uncovered or until clearance for the new grade is assured. Support uncovered lines until approval for backfill is granted by the Construction Manager. Report damage to utility lines or subsurface construction immediately to the Construction Manager.

3.1.7 Structural Excavation

Ensure that footing subgrades have been inspected and approved by the Construction Manager prior to concrete placement.

3.2 SELECTION OF BORROW MATERIAL

Select borrow material to meet the requirements and conditions of the particular fill or embankment for which it is to be used. Obtain borrow material from the borrow areas within the limits of the project site, selected by the Contractor or from approved private sources. The

Contractor is responsible for obtaining and delivering borrow material to the project site.

3.3 SHORING

3.3.1 General Requirements

Submit a Shoring and Sheeting plan for approval 15 days prior to starting work. Submit drawings and calculations, certified by a registered professional engineer, describing the methods for shoring and sheeting of excavations. Finish shoring, including sheet piling, and install as necessary to protect workmen, banks, adjacent paving, structures, and utilities. Remove shoring, bracing, and sheeting as excavations are backfilled, in a manner to prevent caving.

3.3.2 Geotechnical Engineer

The Contractor is required to hire a Professional Geotechnical Engineer to design shoring, and provide inspection of excavations and soil/groundwater conditions throughout construction. The Geotechnical Engineer is responsible for performing pre-construction and periodic site visits throughout construction to assess site conditions. The Geotechnical Engineer is responsible for updating the excavation, sheeting and dewatering plans as construction progresses to reflect changing conditions and submit an updated plan if necessary. Submit a monthly written report, informing the Contractor and Construction Manager of the status of the plan and an accounting of the Contractor's adherence to the plan addressing any present or potential problems. The Construction Manager is responsible for arranging meetings with the Geotechnical Engineer at any time throughout the contract duration.

3.4 STOCKPILE AREAS

Keep stockpiles in a neat and well drained condition, giving due consideration to drainage and erosion control at all times. Separately stockpile excavated satisfactory and unsatisfactory materials. Protect stockpiles of satisfactory materials from contamination which may destroy the quality and fitness of the stockpiled material.

3.5 FINAL GRADE OF SURFACES TO SUPPORT CONCRETE

Do not excavate to final grade until just before concrete is to be placed. Only use excavation methods that will leave the foundation rock in a solid and unshattered condition. Roughen the level surfaces, and cut the sloped surfaces, as indicated, into rough steps or benches to provide a satisfactory bond. Protect shales from slaking and all surfaces from erosion resulting from ponding or water flow.

3.6 GROUND SURFACE PREPARATION

3.6.1 General Requirements

Remove and replace unsatisfactory material with satisfactory materials, as directed by the Construction Manager, in surfaces to receive fill or in excavated areas. Scarify the surface to a depth of 2 inches before the fill is started. Plow, step, bench, or break up sloped surfaces steeper than 1 vertical to 4 horizontal so that the fill material will bond with the existing material. When subgrades are less than the specified density, break up the ground surface to a minimum depth of 6 inches, pulverizing,

and compacting to the specified density. When the subgrade is part fill and part excavation or natural ground, scarify the excavated or natural ground portion to a depth of 12 inches and compact it as specified for the adjacent fill.

3.6.2 Frozen Material

Do not place material on surfaces that are frozen, or contain frost.

3.7 UTILIZATION OF EXCAVATED MATERIALS

Dispose of unsatisfactory excavated materials in designated waste disposal or spoil areas. Use satisfactory material from excavations, insofar as practicable, in the construction of fills, embankments, subgrades, and for similar purposes. Do not waste any satisfactory excavated material without specific written authorization. Dispose of satisfactory material, authorized to be wasted, in designated areas approved for surplus material storage or designated waste areas as directed.

3.7.1 Use of Excavated Material as Fill

Excavated material to be used as fill shall be stockpiled or hauled directly to the fill site. Prior to installation as fill, the material shall be tested to determine the maximum dry density (ASTM D 698) or (ASTM D 1557) and optimum moisture content (ASTM D 2216) of the material. The moisture content of the soil shall be adjusted to near optimum moisture content for compaction. Moisture shall be added to the material in a manner that results in a consistent moisture content throughout the fill. Quick tests of moisture content (ASTM D 4643, ASTM D 4944, or ASTM D 4959) shall be performed as required to maintain moisture control during fill placement.

3.8 BURIED TAPE AND DETECTION WIRE

3.8.1 Buried Warning and Identification Tape

Provide buried utility lines with utility identification tape. Bury tape 12 inches below finished grade; under pavements and slabs, bury tape 6 inches below top of subgrade.

3.9 BACKFILLING AND COMPACTION

Place backfill adjacent to any and all types of structures, and compact to at least 95 percent laboratory maximum density (ASTM D 698) for cohesive materials or 98 percent laboratory maximum density for cohesionless materials (ASTM D 698), to prevent wedging action or eccentric loading upon or against the structure. Prepare ground surface on which backfill is to be placed as specified in paragraph GROUND SURFACE PREPARATION. Provide compaction requirements for backfill materials in conformance with the applicable portions of paragraphs GROUND SURFACE PREPARATION. Finish compaction by sheepsfoot rollers, pneumatic-tired rollers, steel-wheeled rollers, vibratory compactors, or other approved equipment.

3.9.1 Trench Backfill

Backfill trenches to the grade shown. Do not backfill trenches until all specified tests are performed.

3.9.1.1 Replacement of Unyielding Material

Replace unyielding material removed from the bottom of the trench with select granular material or bedding material.

3.9.1.2 Replacement of Unstable Material

Replace unstable material removed from the bottom of the trench or excavation with select granular material placed in layers not exceeding 6 inch loose thickness.

3.9.1.3 Bedding and Initial Backfill

Provide bedding of the type and thickness shown. Place initial bedding material and compact it with approved tampers to a height of at least one foot above the utility pipe or conduit. Bring up the bedding backfill evenly on both sides of the pipe for the full length of the pipe. Take care to ensure thorough compaction of the fill under the haunches of the pipe. Compact backfill to top of pipe to 95 percent of ASTM D 698 maximum density. Provide plastic piping with bedding to spring line of pipe. Provide bedding materials as follows:

- a. Clean, coarsely graded natural gravel, crushed stone or a combination thereof, having a classification of SW, GW or GP in accordance with ASTM D 2487 for bedding. Do not exceed maximum particle size of 3/8 inch.

3.9.1.4 Final Backfill

Fill the remainder of the trench, except for special materials for roadways, and railroads with satisfactory material. Place backfill material and compact as follows:

- a. Roadways and Railroads: Place backfill up to the required elevation as specified. Do not permit water flooding or jetting methods of compaction.

3.9.2 Backfill for Appurtenances

After the manhole, catchbasin, inlet, or similar structure has been constructed and the concrete has been allowed to cure, place backfill in such a manner that the structure will not be damaged by the shock of falling earth. Deposit the backfill material, compact it as specified for final backfill, and bring up the backfill evenly on all sides of the structure to prevent eccentric loading and excessive stress.

3.10 SPECIAL REQUIREMENTS

Special requirements for both excavation and backfill relating to the specific utilities are as follows:

3.10.1 Water Lines

Excavate trenches to a depth that provides a minimum cover of 3 feet from the existing ground surface, or from the indicated finished grade, whichever is lower, to the top of the pipe.

3.10.2 Electrical Distribution System

Provide a minimum cover of 24 inches from the finished grade to direct burial cable and conduit or duct line, unless otherwise indicated.

3.10.3 Pipeline Casing

Provide new smooth wall steel pipeline casing under existing railroad by the boring and jacking method of installation. Provide each new pipeline casing, where indicated and to the lengths and dimensions shown, complete and suitable for use with the new piped utility as indicated. Install pipeline casing by dry boring and jacking method as follows:

3.10.3.1 Bore Holes

Mechanically bore holes and case through the soil with a cutting head on a continuous auger mounted inside the casing pipe. Weld lengths of pipe together in accordance with AWS D1.1. Do not use water or other fluids in connection with the boring operation.

3.10.3.2 Cleaning

Clean inside of the pipeline casing of dirt, weld splatters, and other foreign matter which would interfere with insertion of the piped utilities by attaching a pipe cleaning plug to the boring rig and passing it through the pipe.

3.10.3.3 End Seals

After installation of piped utilities in pipeline casing, provide watertight end seals at each end of pipeline casing between pipeline casing and piping utilities. Provide watertight segmented elastomeric end seals.

3.10.4 Rip-Rap Construction

Place rip-rap on filter fabric in the areas indicated. Install riprap to conform to cross sections, lines and grades shown within a tolerance of 0.1 foot.

3.10.4.1 Stone Placement

Place rock for rip-rap on prepared bedding material to produce a well graded mass with the minimum practicable percentage of voids in conformance with lines and grades indicated. Distribute larger rock fragments, with dimensions extending the full depth of the rip-rap throughout the entire mass and eliminate "pockets" of small rock fragments. Rearrange individual pieces by mechanical equipment or by hand as necessary to obtain the distribution of fragment sizes specified above.

3.11 EMBANKMENTS

3.11.1 Earth Embankments

Construct earth embankments from satisfactory materials free of organic or frozen material and rocks with any dimension greater than 3 inches. Place the material in successive horizontal layers of loose material not more than 10 inches in depth. Spread each layer uniformly on a soil surface that has been moistened or aerated as necessary, and scarified or otherwise broken up so that the fill will bond with the surface on which it is placed.

After spreading, plow, disk, or otherwise break up each layer; moisten or aerate as necessary; thoroughly mix; and compact to at least 95 percent laboratory maximum density for cohesive materials (ASTM D 698) or 98 percent laboratory maximum density for cohesionless materials (ASTM D 698).

Finish compaction by sheepfoot rollers, pneumatic-tired rollers, steel-wheeled rollers, vibratory compactors, or other approved equipment.

3.11.1.1 Waste Cell Perimeter Embankment at Crescent Junction

The Waste Cell Perimeter Embankment forms the outside of the waste cell, and will have 3:1 interior slopes, 5:1 exterior slopes, and a 30 ft wide level top. Material from the cell excavation will be used to construct the Waste Cell Perimeter Embankment. The fill shall be tested to determine its maximum dry density in accordance with ASTM D 698, Standard Test Methods for Laboratory Compaction Characteristics of Soil Using Standard Effort, and the moisture content shall be modified to bring the fill to near optimum for compaction.

Construct the Waste Cell Perimeter Embankment as follows:

- 1) Prepare the ground beneath the proposed perimeter embankment by stripping vegetation and loose soil from the site, scarifying and compacting the top six inches of soil.
- 2) Dump and spread fill in loose lifts of nearly uniform thickness, not to exceed 12" compacted. Fill shall be compacted with a minimum 45,000 lb static weight footed roller capable of kneading compaction, with feet a minimum of 6 inches in length.
- 3) At the Contractor's option, the compactor may be equipped with a Computer Aided Earthmoving System, and soil placement and compaction shall be controlled by the CAES.
- 4) Use the CAES to determine and document compaction, or perform soil density tests in accordance with Section 3.14, below.

3.11.1.2 Waste Cell Spoil Material Embankment at Crescent Junction

The Waste Cell Spoil Material Embankment is a fill embankment to be constructed north of the waste cell. The embankment will divert storm water from the Book Cliffs around the waste cell, and shall be constructed of surplus excavated material (spoil material) from the waste cell excavation. Prior to placement, spoil material shall be tested to determine its maximum dry density in accordance with ASTM D 698, Standard Test Methods for Laboratory Compaction Characteristics of Soil Using Standard Effort, and the moisture content shall be modified to bring the fill to near optimum for compaction.

Construct the Waste Cell Spoil Material Embankment as follows:

- 1) Prepare the ground beneath the proposed perimeter embankment by stripping vegetation and loose soil from the site.
- 2) Dump and spread fill in loose lifts of nearly uniform thickness, not to exceed 12" compacted. Compact material with rollers, equipment tracks, or successive passes of scrapers. Fill shall be compacted to a density of 90% of the laboratory determined maximum density in accordance with ASTM D 698.
- 3) Perform soil density tests in accordance with Section 3.14, below.

3.12 SUBGRADE PREPARATION

3.12.1 Proof Rolling

Prior to the placement of fill or stone base material perform proof rolling

to identify soft soil areas. Proof roll the existing subgrade with rubber-tired construction equipment, such as a loaded dump truck or loaded scraper, with a minimum weight of 45,000 lbs. Notify the Construction Manager a minimum of 3 days prior to proof rolling. Perform proof rolling in the presence of the Construction Manager. Undercut rutting or pumping of material as directed by the Construction Manager to a depth of 12 inches and replace with select material.

3.12.2 Construction

Shape subgrade to line, grade, and cross section, and compact as specified. Include plowing, disking, and any moistening or aerating required to obtain specified compaction for this operation. Remove soft or otherwise unsatisfactory material and replace with satisfactory excavated material or other approved material as directed. Excavate rock encountered in the cut section to a depth of 6 inches below finished grade for the subgrade. Bring up low areas resulting from removal of unsatisfactory material or excavation of rock to required grade with satisfactory materials, and shape the entire subgrade to line and grade, in accordance with project plans.

3.12.3 Compaction

Finish compaction by sheepsfoot rollers, pneumatic-tired rollers, steel-wheeled rollers, vibratory compactors, or other approved equipment. Except for paved areas and railroads, compact each layer of the embankment to at least 95 percent of laboratory maximum density (ASTM D 1557).

3.12.3.1 Subgrade for Railroads

Compact subgrade for railroads to at least 95 percent laboratory maximum density for cohesive materials or 98 percent laboratory maximum density for cohesionless materials (ASTM D 1557).

3.12.3.2 Subgrade for Pavements

Compact subgrade for pavements to at least 95 percent laboratory maximum density (ASTM D 1557) for the depth below the surface of the pavement shown. When more than one soil classification is present in the subgrade, thoroughly blend, reshape, and compact the top 6 inches of subgrade.

3.13 FINISHING

Finish the surface of excavations, embankments, and subgrades to a smooth and compact surface in accordance with the lines, grades, and cross sections or elevations shown. Provide the degree of finish for graded areas within 0.1 foot of the grades and elevations indicated except that the degree of finish for subgrades specified in paragraph SUBGRADE PREPARATION. Finish gutters and ditches in a manner that will result in effective drainage. Finish the surface of areas to be turfed from settlement or washing to a smoothness suitable for the application of turfing materials. Repair graded, topsoiled, or backfilled areas prior to acceptance of the work, and re-established grades to the required elevations and slopes.

3.13.1 Subgrade and Embankments

During construction, keep embankments and excavations shaped and drained. Maintain ditches and drains along subgrade to drain effectively at all times. Do not disturb the finished subgrade by traffic or other operation.

The Contractor is responsible for protecting and maintaining the finished subgrade in a satisfactory condition until ballast, subbase, base, or pavement is placed. Do not permit the storage or stockpiling of materials on the finished subgrade. Do not lay subbase, base course, ballast, or pavement until the subgrade has been checked and approved, and in no case place subbase, base, surfacing, pavement, or ballast on a muddy, spongy, or frozen subgrade.

3.13.2 Capillary Water Barrier

Place a capillary water barrier under concrete floors and slabs directly on the subgrade and compact with a minimum of two passes of a vibratory compactor.

3.13.3 Grading Around Structures

Construct areas within 5 feet outside of each building and structure line true-to-grade, shape to drain, and maintain free of trash and debris until final inspection has been completed and the work has been accepted.

3.14 TESTING

Determine field in-place density in accordance with ASTM D 6938. When ASTM D 6938 is used, check the calibration curves and adjust using only the sand cone method as described in ASTM D 1556. Check the calibration of both the density and moisture gauges at the beginning of a job on each different type of material encountered and at intervals as directed by the Construction Manager. When test results indicate, that compaction is not as specified, remove the material, replace and recompact to meet specification requirements. Perform tests on recompacted areas to determine conformance with specification requirements. Provide certified test results that state that the tests and observations were performed by or under the direct supervision of the engineer and that the results are representative of the materials or conditions being certified by the tests. The following number of tests, if performed at the appropriate time, will be the minimum acceptable for each type operation.

3.14.1 In-Place Densities

- a. One test per 5,000 square feet, or fraction thereof, of each lift of fill or backfill areas compacted by other than hand-operated machines.
- b. One test per 500 square feet, or fraction thereof, of each lift of fill or backfill areas compacted by hand-operated machines.

3.14.1.1 In-Place Density Testing of Waste Cell Perimeter Embankment

- a. For material compacted by other than hand-operated machines:
One test per 50,000 square feet or 1,850 cubic yards of material placed, or fraction thereof, a minimum of one test for each lift of fill or backfill, and a minimum of two tests per day.
- b. For material compacted by hand-operated machines:
One test per 500 square feet, or fraction thereof, of each lift of fill or backfill areas.

3.14.1.2 In-Place Density Testing of Waste Cell Spoil Material Embankment

- a. For material compacted by other than hand-operated machines:
One test per 100,000 square feet or 3,700 cubic yards of material placed.
- b. For material compacted by hand-operated machines:
One test per 500 square feet, or fraction thereof, of each lift of fill or backfill areas.

3.14.2 Check Tests on In-Place Densities

If ASTM D 6938 is used, check in-place densities by ASTM D 1556 as follows:

- a. One check test for each 20 tests per ASTM D 6938, of fill or backfill compacted by other than hand-operated machines.
- b. One check test for each 10 tests per ASTM D 6938, of fill or backfill compacted by hand-operated machines.

3.14.3 Optimum Moisture and Laboratory Maximum Density

Perform Laboratory Density and Moisture Content tests (ASTM D 698, ASTM D 1557, and ASTM D 2216) for each type of fill material to determine the optimum moisture and laboratory maximum density values. For small fill areas of 50,000 cubic yards of fill or less, perform one representative test per 5,000 cubic yards of fill and backfill, or when any change in material occurs that may affect the optimum moisture content or laboratory maximum density. For fill areas requiring more than 50,000 cubic yards of fill, perform one representative test per 20,000 cubic yards of fill and backfill, or when any change in material occurs that may affect the optimum moisture content or laboratory maximum density.

3.14.4 Moisture Control

In the stockpile, excavations, or borrow areas, perform moisture tests per to control the moisture content of material being placed as fill. Control of moisture content of fill shall be performed by conducting routine testing of moisture content by one of the following tests:

- o ASTM D 2216 - Standard Test Methods for Laboratory Determination of Water (Moisture) Content of Soil and Rock by Mass (Oven Moisture)
- o ASTM D 4643 - Determination of Water (Moisture) Content of Soil by the Microwave Oven Heating
- o ASTM D 4944 - Field Determination of Water (Moisture) Content of Soil by the Calcium Carbide Gas Pressure Tester
- o ASTM D 4959 - Determination of Water (Moisture) Content of Soil by Direct Heating

During unstable weather, perform tests as dictated by local conditions and approved by the Construction Manager.

3.15 DISPOSITION OF SURPLUS MATERIAL

Surplus material or other soil material not required or suitable for filling or backfilling, and brush and refuse, shall be removed from Government property or disposed of on site as directed by the Construction

Manager.

-- End of Section --

SECTION TABLE OF CONTENTS

DIVISION 31 - EARTHWORK

SECTION 31 00 20

PLACEMENT AND COMPACTION OF TAILINGS AND INTERIM COVER

PART 1 GENERAL

- 1.1 REFERENCES
- 1.2 SUBMITTALS
- 1.3 EQUIPMENT
 - 1.3.1 Scarification Equipment
 - 1.3.2 Compaction Equipment
 - 1.3.3 Steel Wheeled Rollers
 - 1.3.4 Hand Operated Tampers

PART 2 PRODUCTS

- 2.1 TAILINGS MATERIAL
- 2.2 INTERIM COVER SOIL

PART 3 EXECUTION

- 3.1 TAILINGS AND FILL SOIL ASSESSMENT TESTS
 - 3.1.1 Compaction Testing
- 3.2 INSTALLATION
 - 3.2.1 Tailings and Interim Cover Soil Placement
 - 3.2.2 Moisture Control
 - 3.2.3 Compaction
 - 3.2.4 Scarification
 - 3.2.5 Placement of Demolition Debris
- 3.3 CONSTRUCTION TOLERANCES
- 3.4 CONSTRUCTION TESTS
 - 3.4.1 Tailings and Interim Cover Layer Tests
 - 3.4.2 Quick Moisture Tests
 - 3.4.3 Test Results
- 3.5 PROTECTION
 - 3.5.1 Moisture Content
 - 3.5.2 Erosion
 - 3.5.3 Freezing and Desiccation
 - 3.5.4 Retests

-- End of Section Table of Contents --

SECTION 31 00 20

PLACEMENT AND COMPACTION OF TAILINGS AND INTERIM COVER

PART 1 GENERAL

This specification covers placement, compaction and testing requirements for tailings material and interim clean cover layers at Crescent Junction.

1.1 REFERENCES

The publications listed below form a part of this specification to the extent referenced. The publications are referred to within the text by the basic designation only.

ASTM INTERNATIONAL (ASTM)

ASTM D 698	(2000ae1) Laboratory Compaction Characteristics of Soil Using Standard Effort (12,400 ft-lbf/cu ft)
ASTM D 1140	(2000) Amount of Material in Soils Finer than the No. 200 (75-micrometer) Sieve
ASTM D 1556	(2000) Density and Unit Weight of Soil in Place by the Sand-Cone Method
ASTM D 1557	(2002e1) Standard Test Methods for Laboratory Compaction Characteristics of Soil Using Modified Effort (56,000 ft-lbf/cu ft)
ASTM D 1587	(2000) Thin-Walled Tube Sampling of Soils for Geotechnical Purposes
ASTM D 2167	(1994; R 2001) Density and Unit Weight of Soil in Place by the Rubber Balloon Method
ASTM D 2216	(2005) Laboratory Determination of Water (Moisture) Content of Soil and Rock by Mass
ASTM D 2488	(2006) Description and Identification of Soils (Visual-Manual Procedure)
ASTM D 2922	(2005) Density of Soil and Soil-Aggregate in Place by Nuclear Methods (Shallow Depth)
ASTM D 3017	(2005) Water Content of Soil and Rock in Place by Nuclear Methods (Shallow Depth)
ASTM D 3740	(2004a) Minimum Requirements for Agencies Engaged in the Testing and/or Inspection of Soil and Rock as Used in Engineering Design and Construction

ASTM D 422	(1963; R 2002e1) Particle-Size Analysis of Soils
ASTM D 4220	(1995; R 2000) Preserving and Transporting Soil Samples
ASTM D 4318	(2005) Liquid Limit, Plastic Limit, and Plasticity Index of Soils
ASTM D 4643	(2000) Determination of Water (Moisture) Content of Soil by the Microwave Oven Heating
ASTM D 4944	(2004) Field Determination of Water (Moisture) Content of Soil by the Calcium Carbide Gas Pressure Tester
ASTM D 4643	(2000) Determination of Water (Moisture) Content of Soil by Direct Heating
ASTM D 6938	(2007b) In-Place Density and Water Content of Soil and Soil-Aggregate by Nuclear Methods (Shallow Depth)

1.2 SUBMITTALS

Approval is required for submittals with a "G" designation; submittals not having a "G" designation are for information only. All submittals shall be provided to the Construction Manager in accordance with Section 01 33 00 SUBMITTAL PROCEDURES:

SD-03 Product Data

Protection

Equipment

Materials Handling Plan describing the following: processing and placement of the soil; type, model number, weight and critical dimensions of equipment to be used for soil processing, compaction, scarification, and smooth rolling; method of protecting fill materials from changes in moisture content and freezing after placement.

Testing Laboratory

Name and qualifications of the proposed testing laboratory.

SD-06 Test Reports

Tailings/Fill Material Testing

Compaction Testing

Within 24 hours of conclusion of physical tests, 3 copies of test results, including calibration curves and results of calibration tests.

1.3 EQUIPMENT

Tailings and interim fill material shall be installed with equipment capable of scarifying and preparing the ground surface to receive fill, spreading fill material in uniform lifts, and compacting it to the density required by this specification.

1.3.1 Scarification Equipment

Disks, tillers, or other approved means shall be provided to scarify the the ground surface or the surface of each previous lift of fill prior to placement of the next lift. The scarification equipment shall be capable of uniformly disturbing the upper 1 inch of the underlying soil surface to provide good bonding between lifts.

1.3.2 Compaction Equipment

Compaction equipment shall consist of footed rollers or dozers. Footed rollers shall have a minimum weight of 45,000 pounds and at least one tamping foot shall be provided for each 110 square inches of drum surface. The length of each tamping foot from the outside surface of the drum, shall be at least 6 inches. During compaction operations, the spaces between the tamping feet shall be maintained clear of materials which would impair the effectiveness of the tamping foot rollers. Dozers shall have a minimum ground pressure of 1,650 lbs per sq ft.

1.3.3 Steel Wheeled Rollers

A smooth, non-vibratory steel wheeled roller shall be used to produce a smooth compacted surface on the top of the completed interim cover layer, such that direct rainfall causes minimal erosion. Steel wheeled rollers shall weigh a minimum of 20,000 pounds.

1.3.4 Hand Operated Tampers

Hand operated tampers shall consist of rammers or other impact type equipment. Vibratory type equipment will not be allowed.

PART 2 PRODUCTS

2.1 TAILINGS MATERIAL

Tailings material will consist of uranium mill tailings from the Moab Tailings Pile, off-pile contaminated soils, and demolition debris and other waste materials stored in the Pile at Moab. Most of the material will be uranium mill tailings, consisting of contaminated sands, slimes, intermediate material, and cover soil. The tailings material will be excavated, mixed and blended, dried to near optimum moisture content for compaction, loaded in containers, and shipped to Crescent Junction for disposal. Off pile contaminated soil material will be excavated and hauled to the tailings pile and eventually mixed with the tailings. Demolition debris and other waste materials will be excavated, placed in containers, and shipped like the tailings material. In the waste cell, non-soil materials will be placed in the contaminated tailings fill in a manner that will not result in voids in the waste mass.

2.2 INTERIM COVER SOIL

Interim Cover Soil will be soil from the excavation of the Crescent Junction waste cell. It will be material that has been produced on site by modifying the existing overburden soil and weathered Mancos Shale excavated on site. Overburden and weathered Mancos Shale shall be excavated, pulverized, wetted, and mixed to produce a uniform fine-grained soil near optimum moisture content for compaction. Soil shall be free of roots, debris, organic or frozen material, and shall have a maximum clod size of 1 inch at the time of compaction. Interim cover material shall comply with the criteria listed in Table 1.

TABLE 1
REQUIRED PHYSICAL PROPERTIES OF INTERIM COVER SOIL

Property	Test Value	Test Method
Max. particle size (inches)	1	ASTM D 422
Min. percent passing No. 4 sieve	70	ASTM D 422
Min. percent passing No. 200 sieve	20	ASTM D 1140
Min. liquid limit	25	ASTM D 4318
Min. plasticity index	10	ASTM D 4318
Max. plasticity index	40	ASTM D 4318

PART 3 EXECUTION

3.1 TAILINGS AND FILL SOIL ASSESSMENT TESTS

Assessment tests shall be performed on Tailings and on Stockpiled soil for the Interim Cover Layer to assure compliance with specified requirements and to develop compaction requirements for placement. A minimum of three tests for maximum dry density (ASTM D 698) and moisture content (ASTM D 2216) shall be performed for each type of tailings soil observed. A minimum of three assessment tests shall be performed on stockpiled excavated material for use as Interim Cover Soil for each type of soil observed. During placement of Tailings and Interim Cover soil, quick moisture content tests (ASTM D 4643, ASTM D 4944, or ASTM D 4959) shall be performed as required to maintain moisture control.

3.1.1 Compaction Testing

A representative sample from each principal type or combination of blended Tailings materials shall be tested to establish compaction curves using ASTM D 698. A minimum of one set of compaction curves shall be developed per 10,000 cubic yards of Tailings material. A minimum of 5 points shall be used to develop each compaction curve. A representative sample from each type or combination of stockpiled excavated soil for use as Interim Cover soil shall be tested to establish compaction curves using ASTM D 698.

3.2 INSTALLATION

3.2.1 Tailings and Interim Cover Soil Placement

Tailings and Interim Cover soil shall be placed to the lines and grades shown on the drawings. A GPS guided Computer Aided Earthmoving System (CAES) shall be used to direct fill placement such that Tailings and Interim Cover Soil are placed in loose lifts not to exceed 12 inches in thickness after compaction. In areas where hand operated tampers must be

used, the loose lift thickness shall not exceed 4 inches.

3.2.2 Moisture Control

Tailings and Interim Cover shall be placed and compacted within the moisture content range needed to achieve 90% of the laboratory determined maximum dry density of each type of material. The moisture content shall be maintained uniform throughout each lift. Material shall be dried or water added and thoroughly incorporated into the Tailings or Interim Cover Soil as needed to ensure uniformity of moisture content prior to compaction.

3.2.3 Compaction

Tailings and Interim Cover soil shall be compacted to meet the following density requirements:

Tailings - 90% of the laboratory determined maximum dry density as determined by (ASTM D 698).

Interim Cover Layer - 90% of the laboratory determined maximum dry density as determined by (ASTM D 698).

3.2.4 Scarification

Scarification shall be performed on all areas of the upper surface of each lift prior to placement of the next lift. Scarification shall be accomplished with approved equipment. The final lift of Interim Cover soil shall not be scarified. The final lift shall be smooth rolled with at least 3 passes of the smooth steel wheeled roller to provide a smooth surface.

3.2.5 Placement of Demolition Debris

Demolition debris will be placed in the waste cell along with Tailings material. Each container of demolition debris shall be spread in a single layer, not stacked, and placed in a manner that results in a minimum of voids around the debris.

3.3 CONSTRUCTION TOLERANCES

The top surface of the Tailings and Interim Cover Layer shall be no greater than 2 inches above the lines and grades shown on the drawings. No minus tolerance will be permitted.

3.4 CONSTRUCTION TESTS

3.4.1 Tailings and Interim Cover Layer Tests

Compaction shall be verified by the CAES. When compaction of a lift of Tailings or Interim Cover soil is achieved, the CAES will produce a map of the location and thickness of the completed lift. Computer records for each layer of soil placed will constitute documentation of completed lifts and be compiled as construction records.

Perform compaction Verification Tests, in-place density and moisture content tests on compacted fill material, in accordance with the following requirements:

- Verification tests of in-place density shall be performed on the initial layer of Tailings, on the first 5,000 cubic yards of Interim Cover, and on any layers in which the CAES indicates that problems occurred obtaining compaction.

- When verification in-place density and moisture content tests are performed on a soil layer, a minimum of two tests shall be performed per 5,000 cubic yards of fill material placed.

- Compaction and moisture content tests shall be performed in accordance with the following methods:

- o ASTM D 1556 - Density and Unit Weight of Soil in Place by the Sand-Cone Method

- o ASTM D 2216 - Standard Test Methods for Laboratory Determination of Water (Moisture) Content of Soil and Rock by Mass (Oven Moisture)

- o ASTM D 6938 - In-Place Density and Water Content of Soil and Soil-Aggregate by Nuclear Methods (Shallow Depth)

Note: Companion sand cone tests and oven moisture tests must be performed along with nuclear tests until a sufficient number have been performed to demonstrate a clear correlation.

3.4.2 Quick Moisture Tests

Each day that Tailings or Interim Cover soil are being placed, a minimum of one moisture content quick test in accordance with (ASTM D 4643, ASTM D 4944, or ASTM D 4959) shall be performed to maintain moisture control during fill placement.

3.4.3 Test Results

Where the CAES indicates acceptable compaction, the computer output for that lift (lift thickness, location, and compaction), shall be considered proof of satisfactory lift placement. If the CAES indicates that adequate compaction is not achieved, the lift shall be reworked until an acceptable result is achieved. Verification test results of ASTM D 6938, In-Place Density and Water Content of Soil and Soil-Aggregate by Nuclear Methods (Shallow Depth), shall be used to confirm the acceptability of the CAES results.

3.5 PROTECTION

3.5.1 Moisture Content

After lift placement, moisture content shall be maintained until the next lift is placed.

3.5.2 Erosion

Erosion that occurs in the Tailings or Interim Cover layers shall be repaired and grades re-established.

3.5.3 Freezing and Desiccation

Freezing and desiccation of the Tailings and Interim Cover soil shall be prevented. If freezing or desiccation occurs, the affected soil shall be reconditioned as directed.

3.5.4 Retests

Areas that have been repaired shall be retested as directed. Repairs to the Tailings or Interim Cover layers shall be documented including location and volume of soil affected, corrective action taken, and results of retests.

-- End of Section --

SECTION TABLE OF CONTENTS

DIVISION 31 - EARTHWORK

SECTION 31 00 30

PLACEMENT AND COMPACTION OF FINAL CAP LAYERS

PART 1 GENERAL

- 1.1 SCOPE
- 1.2 REFERENCES
- 1.3 SUBMITTALS
- 1.4 EQUIPMENT
 - 1.4.1 Compaction Equipment
 - 1.4.2 Scarification Equipment
 - 1.4.3 Steel Wheeled Rollers
 - 1.4.4 Hand Operated Tampers

PART 2 PRODUCTS

- 2.1 RADON BARRIER LAYER
- 2.2 STONE FOR FINAL COVER LAYERS
- 2.3 FROST PROTECTION LAYER

PART 3 EXECUTION

- 3.1 EXCAVATION, SEGREGATION, AND STOCKPILING OF CAP MATERIALS
- 3.2 INSTALLATION OF RADON BARRIER MATERIAL
 - 3.2.1 Radon Barrier Material
 - 3.2.2 Radon Barrier Material Placement
 - 3.2.3 Moisture Control
 - 3.2.4 Scarification and Dressing of Final Lift Surface
 - 3.2.5 Compaction
 - 3.2.6 Repair of Voids
- 3.3 INSTALLATION OF FROST PROTECTION LAYER SOIL
 - 3.3.1 Frost Protection Material
 - 3.3.2 Frost Protection Layer Placement
 - 3.3.3 Moisture Control
 - 3.3.4 Scarification and Dressing of Final Lift Surface
 - 3.3.5 Compaction
 - 3.3.6 Repair of Voids
- 3.4 INSTALLATION OF ROCK LAYERS
 - 3.4.1 Rock Placement and Compaction
- 3.5 CONSTRUCTION TOLERANCES
- 3.6 CONSTRUCTION TESTS
 - 3.6.1 Material Tests
 - 3.6.2 Initial and Confirmatory Surveys
- 3.7 PROTECTION
 - 3.7.1 Moisture Content
 - 3.7.2 Erosion
 - 3.7.3 Freezing and Desiccation
 - 3.7.4 Retests

-- End of Section Table of Contents --

SECTION 31 00 30

PLACEMENT AND COMPACTION OF FINAL CAP LAYERS

PART 1 GENERAL

1.1 SCOPE

This specification covers material characteristics, placement, compaction, and testing of final cap layers, including:

Radon barrier layer;
Stone infiltration and bio-barrier;
Frost protection layer; and
Rock armoring.

1.2 REFERENCES

The publications listed below form a part of this specification to the extent referenced. The publications are referred to within the text by the basic designation only.

ASTM INTERNATIONAL (ASTM)

ASTM D 1140	(2000) Amount of Material in Soils Finer than the No. 200 (75-micrometer) Sieve
ASTM D 1556	(2000) Density and Unit Weight of Soil in Place by the Sand-Cone Method
ASTM D 698	(2002e1) Laboratory Compaction Characteristics of Soil Using Standard Effort (12,400 ft-lbf/cu ft)
ASTM D 2167	(1994; R 2001) Density and Unit Weight of Soil in Place by the Rubber Balloon Method
ASTM D 2216	(2005) Laboratory Determination of Water (Moisture) Content of Soil and Rock by Mass
ASTM D 2488	(2006) Description and Identification of Soils (Visual-Manual Procedure)
ASTM D 6938	(2007b) In-place Density and Water Content of Soil and Soil-Aggregate by Nuclear Methods (Shallow Depth)
ASTM D 3740	(2004a) Minimum Requirements for Agencies Engaged in the Testing and/or Inspection of Soil and Rock as Used in Engineering Design and Construction
ASTM D 422	(1963; R 2002e1) Particle-Size Analysis of Soils

ASTM D 4220	(1995; R 2000) Preserving and Transporting Soil Samples
ASTM D 4318	(2005) Liquid Limit, Plastic Limit, and Plasticity Index of Soils
ASTM D 4643	(2000) Determination of Water (Moisture) Content of Soil by the Microwave Oven Heating
ASTM D 4944	(2004) Field Determination of Water (Moisture) Content of Soil by the Calcium Carbide Gas Pressure Tester
ASTM D 4643	(2000) Determination of Water (Moisture) Content of Soil by Direct Heating

1.3 SUBMITTALS

Approval is required for submittals with a "G" designation; submittals not having a "G" designation are for information only. All submittals shall be provided to the Construction Manager in accordance with Section 01 33 00 SUBMITTAL PROCEDURES:

SD-03 Product Data

Equipment

Submit specifications for equipment for the processing, scarification, placement, compaction, and smooth rolling of fill, including type, model number, weight and critical dimensions of equipment.

SD-06 Test Reports

Moisture Content and Relative Density Tests of Fill Materials, G;

Moisture Content Tests of Soil Fill, G;

Moisture Content and In-Place Density Tests of Soil Fill (Verification Testing), G;

CAES Soil Placement and Compaction Records, G;

Test reports shall be submitted to the Energy Solutions Construction Quality Control Manager within 48 hours of the completion of soil placement and field testing.

1.4 EQUIPMENT

Equipment used to place and compact the Radon Barrier material and Frost Protection common fill shall not brake suddenly, turn sharply, or be operated at excessive speeds.

1.4.1 Compaction Equipment

Compaction equipment shall consist of footed rollers which have a minimum

weight of 45,000 pounds and at least one foot for each 110 square inches of drum surface. The length of each tamping foot shall be at least 6 inches, from the outside surface of the drum. During compaction operations, the spaces between the tamping feet shall be maintained clear of materials which would impair the effectiveness of the tamping foot rollers.

1.4.2 Scarification Equipment

Disks, rotor tillers, or other approved means shall be provided to scarify the surface of each lift of soil prior to placement of the next lift. The scarification equipment shall be capable of uniformly disturbing the upper 1 - 2 inches of the soil surface to provide good bonding between lifts.

1.4.3 Steel Wheeled Rollers

A smooth, non-vibratory steel wheeled roller shall be used to produce a smooth compacted surface on finished compacted soil layers. Steel wheeled rollers shall weigh a minimum of 20,000 pounds.

1.4.4 Hand Operated Tampers

Hand operated tampers shall consist of rammers or other impact type equipment. Vibratory type equipment will not be allowed.

PART 2 PRODUCTS

2.1 RADON BARRIER LAYER

Radon Barrier is the layer constructed on top of the interim cover layer and the contaminated tailings material in the waste cell and underlying the protection layers in the final cap. The purpose of this layer is to retard the emanation of radon gas from the tailings into the atmosphere and to minimize infiltration of incident precipitation into the tailings material.

Radon Barrier Layer soil shall be produced by modifying the weathered Mancos Shale excavated on site. Weathered Mancos Shale shall be excavated, separated from other excavated materials, pulverized, wetted, and mixed to produce a uniform fine-grained fill soil at or above optimum moisture content for compaction. It shall be free of roots, debris, organic or frozen material, and shall have a maximum clod size of 1 inch at the time of compaction. Fill material shall comply with the criteria listed in Table 1. Testing of Radon Barrier soil to verify conformance with the following table is described in Section 3.2.1 Radon Barrier Material.

TABLE 1
REQUIRED PHYSICAL PROPERTIES OF RADON BARRIER FILL SOIL

Property	Test Value	Test Method
Max. particle size (inches)	1	ASTM D 422
Min. percent passing No. 4 sieve	80	ASTM D 422
Min. percent passing No. 200 sieve	50	ASTM D 1140
Min. liquid limit	35	ASTM D 4318
Min. plasticity index	10	ASTM D 4318
Max. plasticity index	40	ASTM D 4318

2.2 STONE FOR FINAL COVER LAYERS

Stone for the final cover layers, infiltration and bio-barrier layer and rock armoring, shall be rock material that has long-term chemical and physical durability. Rock for final cover layers shall achieve an acceptable score for its intended use, in accordance with the following rock scoring and acceptance criteria:

TABLE 2
NRC TABLE OF SCORING CRITERIA FOR ROCK QUALITY

Laboratory Test	Weighing Factor			10	9	8	7	6	5	4	3	2	1	0
	L*	S*	I*											
				Good			Fair			Poor				
Specific Gravity	12	6	9	2.75	2.70	2.65	2.60	2.55	2.50	2.45	2.40	2.35	2.30	2.25
Absorption, %	13	5	2	0.10	0.30	0.50	0.67	0.83	1.0	1.5	2.0	2.5	3.0	3.5
Sodium Sulfate, %	4	3	11	1.0	3.0	5.0	6.7	8.3	10.0	12.5	15.0	20.0	25.0	30.0
LA Abrasion, %	1	8	1	1.0	3.0	5.0	6.7	8.3	10.0	12.5	15.0	20.0	25.0	30.0
Schmitt Hammer	11	13	3	70	65	60	54	47	40	32	24	16	8	0

* L = Limestone, S = Sandstone, I = Igneous

Notes:

- Scores were derived from Tables 6.2, 6.5, and 6.7 of NUREG/CR-2642, Long-Term Survivability of Riprap for Armoring Uranium Mill Tailings and Covers: A Literature Review, 1982.
- Weighing Factors are derived from Table 7 of "Petrographic Investigations of Rock Durability and Comparisons of Various Test Procedures," by G.W. Dupuy, Engineering Geology, July 1965. Weighing factors are based on inverse of ranking of test methods for each rock type. Other tests may be used; weighing factors for these tests may be derived using Table 7, by counting upward from the bottom of the table.
- Test methods should be standardized, if a standard test is available and should be those used in NUREG/CR2642, so that proper correlations can be made.

Rock Acceptance Criteria

An acceptable rock score depends on the intended use of the rock. The rock's score must meet the following criteria:

- For occasionally saturated areas, which include the top and sides of the final cover, the rock must score at least 50% or the rock is rejected. If the rock scores between 50% and 80% the rock may be used, but a larger D50 must be provided (oversizing). If the rock score is 80% or greater, no oversizing is required.
- For frequently saturated areas, which include all channels and buried slope toes, the rock must score 65% or the rock is rejected. If the rock scores between 65% and 80%, the rock may be used, but must be oversized. If the rock score is 80% or greater, no oversizing is required.

Oversize rock as follows;

- Subtract the rock score from 80% to determine the amount of oversizing required. For example, a rock with a rating of 70% will require oversizing of 10 percent (80% - 70% = 10%).
- The D50 of the stone shall be increased by the oversizing percent. For example, a stone with a 10% oversizing factor and a D50 of 12 inches will increase to a D50 of 13.2 inches.
- The final thickness of the stone layer shall increase proportionately to the increased D50 rock size. For example, a layer thickness equals twice the D50, such as when the plans call for 24 inches of stone with a D50 of 12 inches, if the stone D50 increases to 13.2, the thickness of the layer of stone with a D50 of 13.2 should be increased to 26.4 inches.

2.3 FROST PROTECTION LAYER

The Frost Protection Layer is the top soil layer constructed of the waste

cell cover. The purpose of this layer is to protect underlying cover layers from degradation due to environmental factors such as freeze-thaw cycles. The Frost Protection Layer shall be constructed of common fill material, which can be any soil material from the waste cell excavation.

PART 3 EXECUTION

3.1 EXCAVATION, SEGREGATION, AND STOCKPILING OF CAP MATERIALS

Cap materials shall be soil material from the waste cell excavation. Materials shall be excavated, segregated into common fill and weathered Mancos Shale, and stockpiled for use as cap materials. Stockpiles shall be at locations shown in the project plans or as directed by the Construction Manager.

3.2 INSTALLATION OF RADON BARRIER MATERIAL

3.2.1 Radon Barrier Material

The Radon Barrier Layer will be constructed of processed Mancos Shale soil. The soil will be produced on site by processing excavated Mancos Shale into a fine-grained soil and adding water to bring the Mancos Shale soil to near optimum moisture content for compaction. Mancos Shale soil produced for Radon Barrier fill shall be tested to determine its material properties and its maximum dry density and moisture content. As a minimum, perform the following soil tests on each 10,000 cu yds of soil:

ASTM D 4318, Liquid Limit, Plastic Limit, and Plasticity Index of Soils
ASTM D 1140, Amount of Material in Soils Finer than the No. 200 Sieve
ASTM D 698, Standard Test Methods for Laboratory Compaction Characteristics of Soil Using Standard Effort.
ASTM D 2216, Laboratory Determination of Water (Moisture) Content of Soil and Rock by Mass and/or ASTM D 4643, Determination of Water (Moisture) Content of Soil by the Microwave Oven Heating

3.2.2 Radon Barrier Material Placement

Radon Barrier shall be placed to the lines and grades shown on the drawings. The soil shall be placed in loose lifts not to exceed 12 inches in thickness after compaction. In areas where hand operated tampers must be used, the loose lift thickness shall not exceed 4 inches.

3.2.3 Moisture Control

Radon Barrier soil shall be placed and compacted within a moisture content range that will achieve the specified compaction. The moisture content shall be maintained uniform throughout each lift. Water added shall be thoroughly incorporated into the soil to ensure uniformity of moisture content prior to compaction.

3.2.4 Scarification and Dressing of Final Lift Surface

Scarification shall be performed on all areas of the upper surface of each underlying soil layer prior to placement of the next lift. Scarification shall be accomplished with approved equipment. The final lift of Radon Barrier soil shall not be scarified. The final lift shall be smooth rolled with at least 3 passes of the approved smooth steel wheeled roller to

provide a smooth surface.

3.2.5 Compaction

Radon Barrier soil shall be compacted to at least 95% of its laboratory determined maximum dry density. The Computer Aided Earthmoving System shall be used to direct fill placement, monitor compaction, and record the location and thickness of each soil layer being placed.

3.2.6 Repair of Voids

Voids created in the Radon Barrier layer during construction (including, but not limited to, penetrations for test samples, grade stakes, and other penetrations necessary for construction) shall be repaired by removing any unsuitable material, backfilling with soil and compacting by tamping each lift with a steel rod, or by backfilling with bentonite.

3.3 INSTALLATION OF FROST PROTECTION LAYER SOIL

3.3.1 Frost Protection Material

The Frost Protection layer will be constructed of common fill soil. The soil will be produced on site by adding water to bring the excavated and stockpiled soil to near optimum moisture content for compaction. Test soil in accordance with ASTM D 698, Laboratory Compaction Characteristics of Soil Using Standard Effort. Perform at least 3 tests on each type of material stockpiled for use as fill. Perform additional lab density tests on stockpiled material if changes in material characteristics are observed.

3.3.2 Frost Protection Layer Placement

Frost Protection soil shall be placed to the lines and grades shown on the drawings. The soil shall be placed in loose lifts not to exceed 12 inches in thickness after compaction. In areas where hand operated tampers must be used, the loose lift thickness shall not exceed 4 inches.

3.3.3 Moisture Control

Frost Protection soil shall be placed and compacted within a moisture content range that will achieve the specified compaction. The moisture content shall be maintained uniform throughout each lift. Water added shall be thoroughly incorporated into the soil to ensure uniformity of moisture content prior to compaction.

3.3.4 Scarification and Dressing of Final Lift Surface

Scarification shall be performed on all areas of the upper surface of each underlying soil layer prior to placement of the next lift. Scarification shall be accomplished with approved equipment. The final lift of soil shall not be scarified. The final lift shall be smooth rolled with at least 3 passes of the approved smooth steel wheeled roller to provide a smooth surface.

3.3.5 Compaction

Soil shall be compacted to 90% of the laboratory determined maximum dry density in accordance with ASTM D 698. The Computer Aided Earthmoving System shall be used to direct fill placement, monitor compaction, and record the location and thickness of each soil layer being placed.

3.3.6 Repair of Voids

Voids created in the Radon Barrier layer during construction (including, but not limited to, penetrations for test samples, grade stakes, and other penetrations necessary for construction) shall be repaired by removing any unsuitable material, backfilling with soil and compacting by tamping each lift with a steel rod, or by backfilling with bentonite.

3.4 INSTALLATION OF ROCK LAYERS

This section describes the material and installation of rock layers for the Infiltration and Biobarrier and Rock Armoring of the final cover.

3.4.1 Rock Placement and Compaction

Rock shall be spread to the thickness indicated on the drawings or in accordance with oversizing due to scoring criteria (see Section 2.2 of this specification). Rock placement shall be guided by the Computer Aided Earthmoving System to ensure that the appropriate thickness has been placed at all locations. Stone with a D50 of 2 inches or less shall be shall be compacted with a vibratory steel drum.

3.5 CONSTRUCTION TOLERANCES

The top surface of the each layer shall be no greater than 2 inches above the lines and grades shown on the drawings. No minus tolerance will be permitted.

3.6 CONSTRUCTION TESTS

3.6.1 Material Tests

For placement and compaction of soils, moisture content tests shall be performed daily prior to placement to maintain moisture control and uniformity of soil to be used for fill. Computer Aided Earthmoving System shall be used to place, compact and document compaction of all soil layers.

CAES acceptance of an installed layer of soil will constitute proof of satisfactory compaction. Computer output of the CAES will be acceptable documentation for location, thickness and compaction of installed layers.

Compaction Verification Tests - Perform in-place density and moisture content tests on compacted fill material in accordance with the following requirements:

- Verification tests of in-place density shall be performed on initial layer of soil placed, and on any layers in which the CAES indicates that problems occurred obtaining compaction.
- When verification in-place density and moisture content tests are performed on a soil layer, a minimum of two tests shall be performed per 5,000 cubic yards of fill material placed.
- Compaction and moisture content tests shall be performed in accordance with the following methods:

ASTM D 1556 - Density and Unit Weight of Soil in Place by the Sand-Cone Method

ASTM D 2216 - Standard Test Methods for Laboratory Determination of Water (Moisture) Content of Soil and Rock by Mass

ASTM D 6938(2007b) - In-place Density and Water Content of Soil and Soil-Aggregate by Nuclear Methods (Shallow Depth)

Note: Companion sand cone tests and oven moisture tests must be performed along with nuclear tests until a sufficient number have been performed to demonstrate a clear correlation.

3.6.2 Initial and Confirmatory Surveys

Verification of the thickness of the Radon Barrier Layer will be performed by comparing before and after surveys of the Layer. Prior to placement of the Radon Barrier Layer, a survey shall be performed of the top of the Interim Cover layer. The initial survey will document the pre-cap geometry of the site. After the Radon Barrier Layer has been installed, a post-installation survey will be performed on the top of the Radon Barrier fill to confirm that the total fill thickness is in accordance with the plans and specifications.

3.7 PROTECTION

3.7.1 Moisture Content

After placement, moisture content shall be maintained or adjusted to meet criteria.

3.7.2 Erosion

Erosion that occurs in the fill layers shall be repaired and grades re-established.

3.7.3 Freezing and Desiccation

Freezing and desiccation of the Radon Barrier layer shall be prevented. If freezing or desiccation occurs, the affected soil shall be removed or reconditioned as directed.

3.7.4 Retests

Areas that have been repaired shall be retested as directed. Repairs to the Radon Barrier layer shall be documented including location and volume of soil affected, corrective action taken, and results of retests.

-- End of Section --

SECTION TABLE OF CONTENTS

DIVISION 31 - EARTHWORK

SECTION 31 32 11

SURFACE-WATER MANAGEMENT AND EROSION CONTROL

PART 1 GENERAL

- 1.1 SCOPE
- 1.2 SUBMITTALS

PART 2 PRODUCTS

- 2.1 SILT FENCE
- 2.2 EROSION MAT
- 2.3 OTHER MATERIALS
- 2.4 EQUIPMENT

PART 3 EXECUTION

- 3.1 INSTALLATION
- 3.2 ADDITIONAL REQUIREMENTS
- 3.3 MAINTENANCE
- 3.4 INSPECTIONS

-- End of Section Table of Contents --

SECTION 31 32 11

SURFACE-WATER MANAGEMENT AND EROSION CONTROL

PART 1 GENERAL

1.1 SCOPE

This section includes materials and placement of silt fence, erosion mat, check dams, construction entrances, diversions, ditches, channels, berms, and stabilization; and maintenance of sedimentation basins and surface-water management and erosion control measures.

1.2 SUBMITTALS

Approval is required for submittals with a "G" designation; submittals not having a "G" designation are for information only. All submittals shall be provided to the Construction Manager in accordance with Section 01 33 00 SUBMITTAL PROCEDURES:

SD-03 Product Data

Manufacturer's data on silt fence;

Manufacturer's data on erosion control matting;

SD-08 Manufacturer's Instructions

Manufacturer's installation and maintenance instructions;

PART 2 PRODUCTS

2.1 SILT FENCE

Furnish silt fence with either woven or nonwoven geotextile. Silt fence shall be:

- a. Woven geotextile consisting of slit films of polypropylene treated with ultraviolet light stabilizers, or nonwoven geotextile consisting of long chain polymeric filaments or polyester yarns, inert to chemicals commonly found in soils and to hydrocarbons, and resistant to mildew, rot, insects, and rodent attack.
- b. Reinforcement Backing: Shall be minimum 14-gauge steel wire and maximum mesh spacing of 6 inches or synthetic netting of equal strength. Use reinforcement backing can be eliminated if post spacing is a maximum of 6 feet and the geotextile tensile strength is at least 200 pounds.
- c. Posts: Shall be either wood or steel with minimum length of 4 feet. Wood posts shall be at least 2 inches by 2 inches of oak or similar hardwood. Steel posts shall be round or shaped as a "U", "T", or "C". Steel posts shall have a minimum weight of 1.33 pounds per linear foot and shall have projections for fastening reinforcement to silt fence.

- d. Wire Staples: Shall be at least 9-gauge thickness with a minimum length of 1 inch.
- e. A preassembled silt fence meeting the material requirements may be used instead of a field constructed silt fence.

2.2 EROSION MAT

Furnish erosion mat that shall be a woven blanket-like fabric made of biodegradable yarn with the following material properties:

- a. Material Content: Coir Yarn: 100 percent; containing 45% Lignin, 55% Cellulose (approximately)
- b. Weight: Minimum 22.7 ounces per square yard;
- c. Open Area: 38 percent (approximately); and
- d. Average Mesh Opening: 0.4" X 0.5"

Furnish erosion mat that will resist degradation for a minimum 6-month period after installation.

Furnish erosion mat having a permissible velocity of 7 ft per second.

2.3 OTHER MATERIALS

- a. Culverts shall be in accordance with Section 33 40 01 STORM DRAINAGE.
- b. Construction entrances shall be in accordance with design plans and details.
- c. Tackifiers or crusting agents shall be used to reduce soil erosion as directed by the Construction Manager.
- d. Materials for other surface-water management and erosion controls shall be in accordance with design plans and details.

2.4 EQUIPMENT

Furnish equipment to perform work specified in this section.

PART 3 EXECUTION

3.1 INSTALLATION

- a. Install silt fence in accordance with Manufacturer's Instructions.
- b. Install check dams in ditches and channels in accordance with project plans and details.
- c. Tackifiers or crusting agents shall be applied in accordance with manufacturer's application instructions.
- d. Construct channels, ditches, and other earthwork as shown on the construction drawings and in accordance with the Contractor's Surface-Water Management and Erosion Control Work Plan. Earthwork for

channels, ditches, and berms shall be in accordance with Section 31 00 00 EARTHWORK.

3.2 ADDITIONAL REQUIREMENTS

Prevent the runoff of polluting substances such as silt, clay, fuels, oils, and contaminated soils from migrating into water supplies and surface waters.

Remove accumulated silt and debris from behind the face of the silt fence when the silt deposits reach approximately one half the height of the fence. Replace silt fence geotextile damaged during maintenance operations. Removed silt and debris shall be placed in locations approved by the Construction Manager.

3.3 MAINTENANCE

Clean, maintain, repair, and replace surface-water management and erosion controls for the duration of the contract in accordance with the Contractor's Surface-Water Management and Erosion Control Work Plan.

3.4 INSPECTIONS

Inspect surface-water management and erosion control measures and sedimentation basins to evaluate their effectiveness and need for maintenance. Any required repairs to the surface-water management and erosion control measures and sedimentation basins shall be initiated upon discovery, but no later than 24 hours after discovery. Inspections shall occur, at a minimum, at the following frequencies:

- a. Weekly
- b. Daily after each rain event exceeding 0.5 in.
- c. Daily during prolonged rainfall events.

Records of inspections shall be kept on file on site by Contractor and shall be submitted monthly to the Construction Manager. The records of inspection shall include the following:

- a. Summary of the scope of the inspection.
- b. Name of inspector.
- c. Inspection date.
- d. Inspection location.
- e. Purpose of the inspection (e.g., regular weekly, following a storm, etc.).
- f. Observations relative to performance of the surface-water management and erosion control measures.
- g. Any necessary corrective actions.
- h. Corrective actions completed and their performance since the previous inspection.

-- End of Section --

SECTION TABLE OF CONTENTS

DIVISION 32 - EXTERIOR IMPROVEMENTS

SECTION 32 11 23

AGGREGATE AND RIPRAP

PART 1 GENERAL

- 1.1 REFERENCES
- 1.2 DEFINITIONS
 - 1.2.1 Untreated Base Course
 - 1.2.2 Degree of Compaction
- 1.3 SUBMITTALS
- 1.4 SAMPLING AND TESTING
 - 1.4.1 Sampling
 - 1.4.2 Tests
 - 1.4.2.1 Sieve Analysis
 - 1.4.2.2 Liquid Limit and Plasticity Index
 - 1.4.2.3 Moisture-Density Determinations
 - 1.4.2.4 Field Density Tests
 - 1.4.2.5 Wear Test
 - 1.4.2.6 Soundness
 - 1.4.3 Testing Frequency
 - 1.4.3.1 Tests on Proposed Material
 - 1.4.4 Approval of Material
- 1.5 WEATHER EFFECTS
- 1.6 PLANT, EQUIPMENT, AND TOOLS

PART 2 PRODUCTS

- 2.1 AGGREGATES
 - 2.1.1 Road Base
 - 2.1.2 Pipe Bedding
 - 2.1.3 Drainage Stone
 - 2.1.4 Riprap
 - 2.1.5 STONE FOR FINAL COVER LAYERS
 - 2.1.6 Stone Layers for the Waste Cell Final Cover
 - 2.1.6.1 Biobarrier and Cover Top
 - 2.1.6.2 Final Cover Edge Riprap
 - 2.1.6.3 Channel Armor Riprap

PART 3 EXECUTION

- 3.1 GENERAL REQUIREMENTS
- 3.2 OPERATION OF AGGREGATE SOURCES
- 3.3 STOCKPILING MATERIAL
- 3.4 PREPARATION OF UNDERLYING COURSE
- 3.5 INSTALLATION OF UNTREATED BASE COURSE
 - 3.5.1 Placing
 - 3.5.2 Grade Control
 - 3.5.3 Compaction of Untreated Base Course
 - 3.5.4 Thickness
 - 3.5.5 Finishing
 - 3.5.6 Smoothness of Base Stone for Pavement

- 3.6 INSTALLATION OF RIPRAP
- 3.7 TRAFFIC
- 3.8 MAINTENANCE
- 3.9 DISPOSAL OF UNSATISFACTORY MATERIALS

-- End of Section Table of Contents --

SECTION 32 11 23

AGGREGATE AND RIPRAP

PART 1 GENERAL

1.1 REFERENCES

The publications listed below form a part of this specification to the extent referenced. The publications are referred to in the text by basic designation only.

AMERICAN ASSOCIATION OF STATE HIGHWAY AND TRANSPORTATION OFFICIALS (AASHTO)

- AASHTO T 11 (2005) Standard Method of Test for Materials Finer than 75-um (No. 200) Sieve in Mineral Aggregates by Washing
- AASHTO T 19 (2004) Standard Method of Test for Bulk Density ("Unit Weight") and Voids in Aggregate
- AASHTO T 27 (2006) Standard Method of Test for Sieve Analysis of Fine and Coarse Aggregates
- AASHTO T 89 (2002) Standard Method of Test for Determining the Liquid Limit of Soils
- AASHTO T 90 (2004) Standard Method of Test for Determining the Plastic Limit and Plasticity Index of Soils
- AASHTO T 99 (2001; R 2004) Moisture-Density Relations of Soils Using a 2.5-kg (5.5-lb) Rammer and a 305-mm (12-in) Drop
- AASHTO T 180 (2004) Standard Method of Test for Moisture-Density Relations of Soils Using a 4.54-kg (10-lb) Rammer and a 457-mm (18-in) Drop
- AASHTO T 193 (2003) Standard Method of Test for The California Bearing Ratio
- AASHTO T 224 (2001; R 2004) Correction for Coarse Particles in the Soil Compaction Test

ASTM INTERNATIONAL (ASTM)

- ASTM C 1260 (2005a) Standard Test Method for Potential Alkali Reactivity of Aggregates (Mortar-Bar Method)
- ASTM C 127 (2004) Standard Test Method for Density,

	Relative Density (Specific Gravity), and Absorption of Coarse Aggregate
ASTM C 128	(2004a) Standard Test Method for Density, Relative Density (Specific Gravity), and Absorption of Fine Aggregate
ASTM C 131	(2006) Standard Test Method for Resistance to Degradation of Small-Size Coarse Aggregate by Abrasion and Impact in the Los Angeles Machine
ASTM C 29/C 29M	(1997; R 2003) Standard Test Method for Bulk Density ("Unit Weight") and Voids in Aggregate
ASTM C 88	(2005) Standard Test Method for Soundness of Aggregates by Use of Sodium Sulfate or Magnesium Sulfate
ASTM D 698	(2000ae1) Laboratory Compaction Characteristics of Soil Using Standard Effort (12,400 ft-lbf/cu ft)
ASTM D 1556	(2000) Density and Unit Weight of Soil in Place by the Sand-Cone Method
ASTM D 1557	(2002e1) Standard Test Methods for Laboratory Compaction Characteristics of Soil Using Modified Effort (56,000 ft-lbf/ft ³) (2700 kN-m/m ³)
ASTM D 2167	(1994; R 2001) Density and Unit Weight of Soil in Place by the Rubber Balloon Method
ASTM D 2487	(2006) Soils for Engineering Purposes (Unified Soil Classification System)
ASTM D 6938	(2007b) In-Place Density and Water Content of Soil and Soil-Aggregate by Nuclear Methods (Shallow Depth)
ASTM D 75	(2003) Standard Practice for Sampling Aggregates
ASTM E 11	(2004) Wire Cloth and Sieves for Testing Purposes

1.2 DEFINITIONS

For the purposes of this specification, the following definitions apply.

1.2.1 Untreated Base Course

Untreated Base Course (UBC) is well graded, durable aggregate uniformly moistened and mechanically stabilized by compaction.

1.2.2 Degree of Compaction

Degree of compaction required, except as noted in the second sentence, is expressed as a percentage of the maximum laboratory dry density obtained by the test procedure presented in AASHTO T 99 or AASHTO T 180 abbreviated as a percent of laboratory maximum dry density. The degree of compaction for material having more than 30 percent by weight of their particles retained on the 3/4 inch sieve shall be expressed as a percentage of the laboratory maximum dry density in accordance with AASHTO T 99 or AASHTO T 180 Method D and corrected with AASHTO T 224.

1.3 SUBMITTALS

Approval is required for submittals with a "G" designation; submittals not having a "G" designation are for information only. All submittals shall be provided to the Construction Manager in accordance with Section 01 33 00 SUBMITTAL PROCEDURES:

SD-06 Test Reports

Sampling and Testing, G;

Field Density Tests, G;

Certified copies of test results for approval not less than 10 days before material is required for the work.

Calibration curves and related test results prior to using the device or equipment being calibrated.

Copies of field test results within 24 hours after the tests are performed.

1.4 SAMPLING AND TESTING

Sampling and testing shall be the responsibility of the Contractor. The materials shall be tested to establish compliance with the specified requirements; testing shall be performed at the specified frequency. The Contracting Officer may specify the time and location of the tests. Copies of test results shall be furnished to the Contracting Officer within 24 hours of completion of the tests.

1.4.1 Sampling

Samples for laboratory testing shall be taken in conformance with ASTM D 75. When deemed necessary, the sampling will be observed by the Contracting Officer.

1.4.2 Tests

The following tests shall be performed in conformance with the applicable standards listed.

1.4.2.1 Sieve Analysis

Sieve analysis shall be made in conformance with AASHTO T 27 and AASHTO T 11. Sieves shall conform to ASTM E 11.

1.4.2.2 Liquid Limit and Plasticity Index

Liquid limit and plasticity index shall be determined in accordance with AASHTO T 89 and AASHTO T 90.

1.4.2.3 Moisture-Density Determinations

The laboratory maximum dry density and optimum moisture content shall be determined in accordance with AASHTO T 99 or AASHTO T 180, Method D and corrected with AASHTO T 224.

1.4.2.4 Field Density Tests

Density shall be field measured in accordance with ASTM D 1556, ASTM D 2167 or ASTM D 6938. For the method presented in ASTM D 6938 the calibration curves shall be checked and adjusted if necessary using only the sand cone method as described in paragraph Calibration, of the ASTM publication. Tests performed in accordance with ASTM D 6938 result in a wet unit weight of soil and when using this method, ASTM D 6938 shall be used to determine the moisture content of the soil. The calibration curves furnished with the moisture gauges shall also be checked along with density calibration checks as described in ASTM D 6938. The calibration checks of both the density and moisture gauges shall be made by the prepared containers of material method, as described in paragraph Calibration of ASTM D 6938, on each different type of material being tested at the beginning of a job.

1.4.2.5 Wear Test

Wear tests shall be made on aggregate material in conformance with ASTM C 131.

1.4.2.6 Soundness

Soundness tests shall be made on aggregate in accordance with ASTM C 88.

1.4.3 Testing Frequency

1.4.3.1 Tests on Proposed Material

To demonstrate that the proposed material meets all specified requirements, one of each of the following tests shall be performed on the proposed material prior to commencing construction, and subsequently for every 5,000 cubic yards of material. If materials from more than one source are going to be utilized, this testing shall be completed for each source.

- a. Sieve Analysis.
- b. Liquid limit and plasticity index.
- c. Moisture-density relationship.
- d. Wear.
- e. Soundness.

1.4.4 Approval of Material

The source of the material shall be selected prior to the time the material will be required in the work. Approval of material will be based on test

results.

1.5 WEATHER EFFECTS

Completed areas damaged by freezing, rainfall, or other weather conditions shall be corrected to meet specified requirements.

1.6 PLANT, EQUIPMENT, AND TOOLS

All plant, equipment, and tools used in the performance of the work shall be subject to approval before the work is started and shall be maintained in satisfactory working condition at all times. The equipment shall be adequate and shall have the capability of producing the required compaction, meeting grade controls, thickness control, and smoothness requirements as set forth herein.

PART 2 PRODUCTS

2.1 AGGREGATES

Aggregate shall consist of clean, sound, durable particles of crushed stone, crushed gravel, angular sand, or other approved material. Untreated Base Course shall be free of lumps of clay, organic matter, and other objectionable materials or coatings. Gravel shall be free of silt and clay as defined by ASTM D 2487, organic matter, and other objectionable materials or coatings. Aggregates will be used for the following applications, and the material properties for each of these application will be provided in the following section:

Application	Name of Material	Gradation
Road Base	Untreated Base Course	UDOT UBC
Pipe Bedding	Coarse sand/gravel	ASTM D448 #9
Drainage Stone	Open graded gravel	ASTM D448 #57
Riprap slope armor	Riprap	D50 per plans
Riprap channel armor	Riprap	D50 per plans
Cover Biobarrier	Sandy gravel	D50 2 in
Cover Top	Sandy gravel	D50 2 in
Cover Apron Riprap	Riprap, 1,000 yr	D50 per plans
Cover Slope Riprap	Riprap, 1,000 yr	D50 per plans
CJ Channel Armor	Riprap, 1,000 yr	D50 per plans

2.1.1 Road Base

Aggregate for road base beneath asphalt pavement and for unpaved gravel roads and pads shall be UDOT Untreated Base Course. The UBC coarse aggregate shall not show more than 50 percent loss when subjected to the Los Angeles abrasion test in accordance with ASTM C 131. The amount of flat and elongated particles shall not exceed 30 percent. A flat particle is one having a ratio of width to thickness greater than 3; an elongated particle is one having a ratio of length to width greater than 3. In the portion retained on each sieve specified, the crushed aggregates shall contain at least 50 percent by weight of crushed pieces having two or more freshly fractured faces with the area of each face being at least equal to 75 percent of the smallest midsectional area of the piece. When two fractures are contiguous, the angle between planes of the fractures must be at least 30 degrees in order to count as two fractured faces. Crushed gravel for road base shall be provided in the gradation listed in TABLE 1. When the coarse aggregate is supplied from more than one source, aggregate

from each source shall meet the specified requirements and shall be stockpiled separately.

2.1.2 Pipe Bedding

Pipe bedding shall be coarse sand, or fine gravel, free from deleterious materials and rocks larger than 3/8 inch. Sandy soil or excavated shaly soil may be used for pipe bedding if it is excavated or processed such that the material size is similar to the gradation listed in TABLE 1.

2.1.3 Drainage Stone

Drainage stone is an open graded stone material intended as a capillary break beneath concrete slabs. Drainage stone will also be used for French Drains and seepage collection drains for retaining structures and mechanically stabilized earth structures. Drainage stone shall be provided in the gradation listed in TABLE 1.

2.1.4 Riprap

Riprap for slope and channel protection shall be provided at locations indicated on the drawings. Riprap shall be sized in accordance with plans and as listed in TABLE 1.

TABLE I. GRADATION OF AGGREGATES

Percentage by Weight Passing Square-Mesh Sieve

Sieve Designation	Road Base	Pipe Bedding	Drainage Stone	Riprap Slope Armor	Riprap Channel Armor
12 inch	-----	-----	-----	-----	100
10 inch	-----	-----	-----	100	80-100
8 inch	-----	-----	-----	80-100	20-80
6 inch	-----	-----	-----	20-60	0-20
4 inch	-----	-----	-----	0-20	0
2 inch	-----	-----	-----	0	-----
1-1/2 inch	100	-----	100	-----	-----
1 inch	90-100	-----	95-100	-----	-----
3/4 inch	70-85	-----	-----	-----	-----
1/2 inch	65-80	-----	25-60	-----	-----
3/8 inch	55-75	100	-----	-----	-----
No. 4	40-65	85-100	0-10	-----	-----
No. 8	-----	20-40	0-5	-----	-----
No. 16	25-40	10-20	0	-----	-----
No. 50	-----	5-10	-----	-----	-----
No. 200	7-11	0-5	-----	-----	-----

2.1.5 STONE FOR FINAL COVER LAYERS

Stone for the final cover layers, infiltration and bio-barrier layer and rock armoring, shall be rock material that has long-term chemical and physical durability. Rock for final cover layers shall achieve an acceptable score for its intended use, in accordance with the following rock scoring and acceptance criteria:

TABLE 2
NRC TABLE OF SCORING CRITERIA FOR ROCK QUALITY

Laboratory Test	Weighing Factor		10	9	8	7	6	5	4	3	2	1	0
	L*	S* I'											

TABLE 2
NRC TABLE OF SCORING CRITERIA FOR ROCK QUALITY

				Good			Fair			Poor				
Specific Gravity	12	6	9	2.75	2.70	2.65	2.60	2.55	2.50	2.45	2.40	2.35	2.30	2.25
Absorption, %	13	5	2	0.10	0.30	0.50	0.67	0.83	1.0	1.5	2.0	2.5	3.0	3.5
Sodium Sulfate, %	4	3	11	1.0	3.0	5.0	6.7	8.3	10.0	12.5	15.0	20.0	25.0	30.0
LA Abrasion, %	1	8	1	1.0	3.0	5.0	6.7	8.3	10.0	12.5	15.0	20.0	25.0	30.0
Schmidt Hammer	11	13	3	70	65	60	54	47	40	32	24	16	8	0

* L = Limestone, S = Sandstone, I = Igneous

Notes:

1. Scores were derived from Tables 6.2, 6.5, and 6.7 of NUREG/CR-2642, Long-Term Survivability of Riprap for Armoring Uranium Mill Tailings and Covers: A Literature Review, 1982.
2. Weighing Factors are derived from Table 7 of "Petrographic Investigations of Rock Durability and Comparisons of Various Test Procedures," by G.W. Dupuy, Engineering Geology, July 1965. Weighing factors are based on inverse of ranking of test methods for each rock type. Other tests may be used; weighing factors for these tests may be derived using Table 7, by counting upward from the bottom of the table.
3. Test methods should be standardized, if a standard test is available and should be those used in NUREG/CR2642, so that proper correlations can be made.

Rock Acceptance Criteria

An acceptable rock score depends on the intended use of the rock. The rock's score must meet the following criteria:

- For occasionally saturated areas, which include the top and sides of the final cover, the rock must score at least 50% or the rock is rejected. If the rock scores between 50% and 80% the rock may be used, but a larger D50 must be provided (oversizing). If the rock score is 80% or greater, no oversizing is required.
- For frequently saturated areas, which include all channels and buried slope toes, the rock must score 65% or the rock is rejected. If the rock scores between 65% and 80%, the rock may be used, but must oversized. If the rock score is 80% or greater, no oversizing is required.

Oversize rock as follows;

- Subtract the rock score from 80% to determine the amount of oversizing required. For example, a rock with a rating of 70% will require oversizing of 10 percent (80% - 70% = 10%).
- The D50 of the stone shall be increased by the oversizing percent. For example, a stone with a 10% oversizing factor and a D50 of 12 inches will increase to a D50 of 13.2 inches.
- The final thickness of the stone layer shall increase proportionately to the increased D50 rock size. For example, a layer thickness equals twice the D50, such as when the plans call for 24 inches of stone with a D50 of 12 inches, if the stone D50 increases to 13.2, the thickness of the layer of stone with a D50 of 13.2 should be increased to 26.4 inches.

2.1.6 Stone Layers for the Waste Cell Final Cover

Stone shall be provided and installed for the following Final Cover Layers:

Application	Type of Material	Material Size
Cover Biobarrier	Sandy gravel	D50 2 in
Cover Top	Sandy gravel	D50 2 in
Cover South Edge	Riprap, 1,000 yr	D50 12"
Cover N,E,& W Edges	Riprap, 1,000 yr	D50 8"
CJ Channel Armoring	Riprap, 1,000 yr	D50 8"

2.1.6.1 Biobarrier and Cover Top

The Biobarrier and Top of Cover Stone shall meet the 1,000 year lifespan

rock scoring criteria and shall be a mix of 2 inch stone and finer materials. The gradation shall be as listed in Table 3, below.

TABLE 3. GRADATION OF FINAL COVER AGGREGATES

Percentage by Weight Passing Square-Mesh Sieve

Sieve Designation	Cover Biobarrier	Cover Top	Cover South Edge Riprap & Bedding	Cover N, E, & W Edge Riprap & Bedding	Crescent Junct. Channel Armor Riprap
18 inch	-----	-----	100	-----	-----
16 inch	-----	-----	80-100	-----	-----
12 inch	-----	-----	30-60	100	100
10 inch	-----	-----	-----	80-100	80-100
8 inch	-----	-----	20-40	30-60	20-80
6 inch	-----	-----	0	20-40	0-20
4 inch	100	100	-----	0	0
2 inch	50-100	50-100	-----	-----	-----
1-1/2 inch	40-50	40-50	100	100	-----
1 inch	20-40	20-40	80-100	80-100	-----
3/4 inch	-----	-----	-----	-----	-----
1/2 inch	15-25	15-25	60-80	60-80	-----
3/8 inch	-----	-----	-----	-----	-----
No. 4	10-20	10-20	30-60	30-60	-----
No. 8	5-15	5-15	20-40	20-40	-----
No. 16	5-10	0-10	10-30	10-30	-----
No. 50	-----	-----	-----	-----	-----
No. 200	0-5	0-5	0-5	0-5	-----

2.1.6.2 Final Cover Edge Riprap

Riprap shall be placed on the Final Cover Edges in accordance with the locations and sizes shown on the Final Cover Plans. The Riprap must meet the 1,000 year lifespan rock scoring criteria. The Cover Edge consists of the slope of the Waste Cell and a 10 ft strip along the top of the slope. The South Edge riprap shall have a D50 of 12" and a bedding layer 4 inches in thickness. The East, West, and North edges shall have a D50 of 8" and a bedding layer 3 inches in thickness. Cover Edge stone gradations are listed in Table 3.

2.1.6.3 Channel Armor Riprap

Channel armor riprap for the channels associated with the Waste Cell shall have riprap armoring in locations and sizes shown in the Final Cover plans and gradation listed. The riprap must meet the 1,000 year lifespan rock scoring criteria. The channel armor riprap shall be installed without a bedding layer.

PART 3 EXECUTION

3.1 GENERAL REQUIREMENTS

Adequate drainage shall be provided during the entire period of construction to prevent water from collecting or standing on the working area. Line and grade stakes shall be provided as necessary for control.

3.2 OPERATION OF AGGREGATE SOURCES

Clearing, stripping, and excavating shall be the responsibility of the

Contractor. The aggregate sources shall be operated to produce the quantity and quality of materials meeting these specifications requirements in the specified time limit.

3.3 STOCKPILING MATERIAL

Prior to stockpiling of material, storage sites shall be cleared and leveled by the Contractor. All materials, including approved material available from excavation and grading, shall be stockpiled in the manner and at the locations designated. Aggregates shall be stockpiled on the cleared and leveled areas designated by the Contracting Officer to prevent segregation. Materials obtained from different sources shall be stockpiled separately.

3.4 PREPARATION OF UNDERLYING COURSE

Prior to constructing the base course(s), the underlying course or subgrade shall be cleaned of all foreign substances. At the time of construction of the base course(s), the underlying course shall contain no frozen material. The surface of the underlying course or subgrade shall meet specified compaction and surface tolerances. The underlying course shall conform to Section 31 00 00 EARTHWORK. Ruts or soft yielding spots in the underlying courses, areas having inadequate compaction, and deviations of the surface from the requirements set forth herein shall be corrected by loosening and removing soft or unsatisfactory material and by adding approved material, reshaping to line and grade, and recompacting to specified density requirements. The finished underlying course shall not be disturbed by traffic or other operations and shall be maintained by the Contractor in a satisfactory condition until the base course is placed.

3.5 INSTALLATION OF UNTREATED BASE COURSE

3.5.1 Placing

The material shall be placed on the prepared subgrade or subbase in layers of uniform thickness. When a compacted aggregate layer 6 inches or less in thickness is required, the material shall be placed in a single layer. When a compacted aggregate layer in excess of 6 inches is required, the material shall be placed in layers of equal thickness. No layer shall be thicker than 6 inches or thinner than 3 inches when compacted. The layers shall be so placed that when compacted they will be true to the grades shown in the plans.

3.5.2 Grade Control

The finished and completed base course shall conform to the lines, grades, and cross sections shown. Underlying material(s) shall be excavated and prepared at sufficient depth for the required base course thickness so that the finished base course and the subsequent surface course will meet the designated grades.

3.5.3 Compaction of Untreated Base Course

Each layer of the Untreated Base Course (UBC) shall be compacted as specified with approved compaction equipment. In all places not accessible to the rollers, the mixture shall be compacted with hand-operated power tampers. Compaction of UBC shall continue until each layer has a degree of compaction that is at least 95 percent of laboratory maximum density through the full depth of the layer. The Contractor shall make such

adjustments in compacting or finishing procedures as may be directed to obtain true grades, to minimize segregation and degradation, to reduce or increase water content, and to ensure a satisfactory base course. Any materials that are found to be unsatisfactory shall be removed and replaced with satisfactory material or reworked, as directed, to meet the requirements of this specification.

3.5.4 Thickness

Compacted thickness of the base course shall be as indicated. No individual layer shall be thicker than 6 inches nor be thinner than 3 inches in compacted thickness.

3.5.5 Finishing

The surface of the top layer of base course shall be finished after final compaction by cutting any overbuild to grade and rolling with a steel-wheeled roller. Thin layers of material shall not be added to the top layer of base course to meet grade. If the elevation of the top layer of base course is 1/2 inch or more below grade, then the top layer should be scarified to a depth of at least 3 inches and new material shall be blended in and compacted to bring to grade.

3.5.6 Smoothness of Base Stone for Pavement

The surface of the top layer shall show no deviations in excess of 1/2 inch when tested with a 12 foot straightedge. Measurements shall be taken in successive positions parallel to the centerline of the area to be paved. Measurements shall also be taken perpendicular to the centerline at 50 foot intervals. Deviations exceeding this amount shall be corrected by removing material and replacing with new material, or by reworking existing material and compacting it to meet these specifications.

3.6 INSTALLATION OF RIPRAP

Riprap shall be placed at locations, thicknesses, and sizes indicated on the drawings. At all locations except the Waste Cell at Crescent Junction, riprap shall be placed over a geotextile in accordance with Section 31 05 19 GEOTEXTILE. For the Waste Cell cover slopes, bedding aggregate shall be placed and the riprap installed over the bedding aggregate.

3.7 TRAFFIC

Completed portions of the base course for pavement may be opened to limited traffic, provided there is no marring or distorting of the surface by the traffic. Heavy equipment shall not be permitted except when necessary to construction, and then the area shall be protected against marring or damage to the completed work.

3.8 MAINTENANCE

The base course shall be maintained in a satisfactory condition until the full pavement section is completed and accepted. Maintenance shall include immediate repairs to any defects and shall be repeated as often as necessary to keep the area intact. Any base course that is not paved over prior to the onset of winter, shall be retested to verify that it still complies with the requirements of this specification. Any area of base course that is damaged shall be reworked or replaced as necessary to comply with this specification.

3.9 DISPOSAL OF UNSATISFACTORY MATERIALS

Any unsuitable materials that must be removed shall be disposed of as directed.

-- End of Section --